


# Optix Surface 1200 Direct - Indirect Medium Output

OPTIX SURFACE 1200x200 2 LINE D/I 3000K ALU DALI  
2023721



## Product features

- OPTIX SURFACE 1200x200 2 LINE D/I 3000K ALU DALI is a high efficacy low glare luminaire for office and education applications. Direct / Indirect lighting with 80% downlight and 20% uplight ratio for ceiling suspended mounting. Size: 1129x200x45mm. Aluminised plastic extra low glare optics in 2 lines configuration. White RAL9016 fixture body. DALI dimmable. 3000K Warm White LED, CRI>80, chromaticity tolerance of 3-step MacAdam ellipse. Luminous flux 4000lm. Power consumption 27.5W. Luminaire efficacy 145lm/W. Lifespan: 60,000 hours L90B10. UGR<16, Luminance at 65°<200 Cd/m<sup>2</sup>, IK07, IP20. Photobiological safety risk group 0. Electrical protection Class I. Glow wire test 850°C.




## PRODUCT OVERVIEW

Product name	OPTIX SURFACE 1200x200 2 LINE D/I 3000K ALU DALI
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Suspended
Fixture rating	Enclosed
General application	Education, Office
ETIM Class	EC002892
Warranty	5 years
Useful luminous flux (Fuse)	4000
Fixture luminous flux (lm)	4000
Luminous flux (lm)	4000
Luminaire efficacy (lm/W)	145
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 16
Photobiological Risk Group	RG0
Total power consumption (W)	27.5
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768237210

**Optix Surface 1200 Direct - Indirect Medium Output**  
*OPTIX SURFACE 1200x200 2 LINE D/I 3000K ALU DALI*  
2023721

## PHOTOMETRY



## TECHNICAL DRAWINGS

