

Product data sheet

Item No. 96.021.4251.4

Female connector with strain relief RST20I2S B13ZRXS L BR01

Splitter connector with RST20I2, 2 pole, double strain relief (feed through wiring), female, screw connection, 50V/20A, for cable diameters 6-10 mm, color of coding: brown, color of housing: black



| | |
|------------|---------------|
| Item No. | 96.021.4251.4 |
| EAN | 4015573907638 |
| Order Unit | 100 Piece(s) |

Certificates / Approvals

Technical data

General

| | |
|----------------------------------|-------|
| Rated current | 20 A |
| Rated voltage | 50 V |
| Rated impulse voltage | 4 kV |
| Pull relief | Yes |
| Pollution degree | 3 |
| Mechanical coding | Yes |
| Interlockable | Yes |
| Color of coding/ contact carrier | Brown |
| Marking of poles | |

Connection Data

| | |
|-----------------------------------|-------------------|
| Connection cross section solid | 4 mm ² |
| Connection cross section stranded | 4 mm ² |
| Terminations per pole | 1 |

Model

| | |
|---------------------------|------------------|
| Model | female |
| Number of poles | 2 |
| Connection type | Screw connection |
| Degree of protection (IP) | IP66/IP68 |

Material

| | |
|--|---------------|
| Housing material | Polyamide |
| Halogen free | Yes |
| Contact material | CuZn |
| Insulation components continuous temperature | 100 °C |
| Surface finish | Silver-plated |

Dimensions

| | |
|--------|-------|
| Length | 96 mm |
| Width | 59 mm |
| Height | 38 mm |

Technical drawing

