



## This item includes:

	<b>Item No.: 206-118</b>		<b>Item No.: 206-804</b>		<b>Item No.: 887-950</b>		<b>Item No.: 206-1125</b>
Cable cutter; f. Cu and Al wires up to 35 mm <sup>2</sup> /AWG 2	1	Testboy; with integrated flashlight	1	Splicing Connector Set; L-BOXX® Mini; 221, 2273, 773, 224, 243 Series	1	Wire stripper "Quickstrip Vario"; Standard, 0.03 mm <sup>2</sup> ... 16 mm <sup>2</sup> ; with wire cutter	1
	<b>Item No.: 206-3000</b>		<b>Item No.: 221-2411/995-012</b>		<b>Item No.: 206-2101</b>		<b>Item No.: 206-3060</b>
Tool bag; empty; compatible with L-BOXX® Micro and Mini; Capacity: 12 kg	1	Inline splicing connector with levers; for all conductor types; max. 4 mm <sup>2</sup> ; 2-conductor; transparent housing; Transparent cover; Surrounding air temperature: max 85°C (T85); 4,00 mm <sup>2</sup> ; transparent	1	VDE screwdriver set; PH1; PH2; PZ1; 2.5; 3.5; 5.5; VDE tested; 1000 V; insulated; 2-component grip	1	Tool bag; empty; Belt pouch	1

## Physical data

Width	330 mm / 12.992 inches
Height	413 mm / 16.26 inches
Depth	220 mm / 8.661 inches

## Material data

Fire load	6.721 MJ
Weight	3194 g

## Commercial data

PU (SPU)	1 pcs
Packaging type	Box
Country of origin	QU
GTIN	4066966669893
Customs tariff number	80808080888

#### Product classification

UNSPSC	27113204
ETIM 9.0	EC000149
ECCN	NO US CLASSIFICATION

#### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

#### Downloads

#### Environmental Product Compliance

##### Compliance Search

Environmental Product  
Compliance  
206-3001/002-004

