



OPTIX RECESSED 1200x300 2L TW ALU DALI

Item No: 2023682

Concord

General data

|                                         |                                        |
|-----------------------------------------|----------------------------------------|
| Product name                            | OPTIX RECESSED 1200x300 2L TW ALU DALI |
| Technology                              | LED (3 SDCM)                           |
| Cap/Base                                | N/A                                    |
| Housing                                 | Steel                                  |
| Mount                                   | Ceiling recessed mounting              |
| Fixture rating                          | Enclosed                               |
| General application                     | Education, Office                      |
| Operating temperature range (°C)        | 10°C...+25°C                           |
| Performance ambient temperature Tq (°C) | 25                                     |
| ETIM Class                              | EC002892                               |
| Warranty                                | 5 years                                |

Optical data

|                                 |                |
|---------------------------------|----------------|
| Useful luminous flux (Φuse)     | 3200           |
| Fixture luminous flux (lm)      | 3200           |
| Luminous flux (lm)              | 3200           |
| Luminaire efficacy (lm/W)       | 107            |
| Light colour                    | Tuneable White |
| CRI (Ra)                        | 80             |
| Colour Variation Initial (SDCM) | SDCM3          |
| Distribution type               | Symmetric      |
| Glare control                   | < 16           |
| Photobiological Risk Group      | RG1            |

Electrical data

|                                                                  |                             |
|------------------------------------------------------------------|-----------------------------|
| Total power consumption (W)                                      | 30                          |
| Primary Supply/Product voltage - min (V)                         | 220                         |
| Primary Supply/Product voltage - max (V)                         | 240                         |
| Lamp power factor                                                | 0.97                        |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 10                          |
| Electrical protection                                            | Class I                     |
| Control gear required                                            | No                          |
| Control gear type                                                | LED driver constant current |
| Dimmable                                                         | Yes                         |
| Dimming method                                                   | DALI                        |
| Drive current (mA)                                               | 600                         |
| Inrush Current (A)                                               | 29                          |
| Inrush Duration (µs)                                             | 180                         |
| Energy Efficiency Class (A->G) of contained light source         | D                           |
| Nominal Frequency (Hz)                                           | 50/60Hz                     |
| LED Flickering Rate                                              | Ultra low (5% or less)      |
| Max. products per 10A C Breaker                                  | 21                          |
| Max. products per 13A C Breaker                                  | 28                          |
| Max. products per 16A C Breaker                                  | 36                          |
| Max. products per 20A C Breaker                                  | 45                          |
| Max. products per 10A B Breaker                                  | 13                          |
| Max. products per 13A B Breaker                                  | 17                          |
| Max. products per 16A B Breaker                                  | 22                          |
| Max. products per 20A B Breaker                                  | 27                          |
| Connectable conductor cross section - Min (mm²)                  | 2.5                         |
| Connectable conductor cross section - Max (mm²)                  | 2.5                         |

Lifetime data

|                  |        |
|------------------|--------|
| Lifespan L70 B50 | 120000 |
| Lifespan L80 B20 | 107500 |
| Lifespan L90 B10 | 48500  |

OPTIX RECESSED 1200x300 2L TW ALU DALI

Item No: 2023682

Concord

Physical data

|                             |                                  |
|-----------------------------|----------------------------------|
| Housing colour              | RAL 9016 - Traffic white / Bezel |
| IP rating                   | IP20                             |
| IK rating                   | IK07                             |
| Diffuser finish             | Matt/satinized                   |
| Diffuser material           | PC Polycarbonate                 |
| Nominal Product Length (mm) | 1196                             |
| Nominal Product Width (mm)  | 296                              |
| Nominal Product Height (mm) | 38                               |
| Weight (kg)                 | 5.0                              |

Packaging

|                                       |                |
|---------------------------------------|----------------|
| Product EAN number                    | 5025768236824  |
| Packaging single length / height (cm) | 124.5          |
| Packaging single width (cm)           | 6.5            |
| Packaging single depth (cm)           | 32.0           |
| DUN14 (inner)                         | 05025768236824 |
| Units per outer package               | 1              |
| Packaging outer length / height (cm)  | 124.5          |
| Packaging outer width (cm)            | 6.5            |
| Packaging outer depth (cm)            | 32.0           |

Safety data

|                                  |       |
|----------------------------------|-------|
| Glow Wire Test (°C)              | 850   |
| Optimal operating condition (°C) | 10-25 |