

Product data sheet

Item No. 96.022.4050.8

Male connector with strain relief RST20i2S
S13ZR1SVL KG06

Connector RST20i2, 2 pole, male, screw connection, 50V/20A, for cable diameters 6-10 mm, color of coding: pebble gray, color of housing: black



| | |
|------------|---------------|
| Item No. | 96.022.4050.8 |
| EAN | 4015573956353 |
| Order Unit | 100 Piece(s) |

Certificates / Approvals



Technical data

General

| | |
|----------------------------------|-------------|
| Rated current | 20 A |
| Rated voltage | 24 V |
| Rated impulse voltage | 4 kV |
| Pull relief | Yes |
| Pollution degree | 3 |
| Mechanical coding | Yes |
| Interlockable | Yes |
| Color of coding/ contact carrier | Pebble gray |
| Marking of poles | |

Connection Data

| | |
|-----------------------------------|-------------------|
| Connection cross section solid | 4 mm ² |
| Connection cross section stranded | 4 mm ² |
| Terminations per pole | 1 |

Model

| | |
|-----------------|------|
| Model | male |
| Number of poles | 2 |

| | |
|---------------------------|------------------|
| Connection type | Screw connection |
| Degree of protection (IP) | IP66/IP68 |

Material

| | |
|--|---------------|
| Housing material | Polyamide |
| Halogen free | Yes |
| Contact material | CuZn |
| Insulation components continuous temperature | 100 °C |
| Surface finish | Silver-plated |

Dimensions

| | |
|--------|---------|
| Length | 80.4 mm |
| Width | 34.6 mm |
| Height | 34.6 mm |

Technical drawing

