

Certificate of Compliance

Certificate Number:

UL-US-L252354-131-
82119002-7

Report Reference:

E252354-20091128

Issue Date:

2024-04-02

Issued to:

ABB France
11 Rue d'Arsonval Chassieu 69680
France

This certificate confirms that representative samples of:
NKCR - Auxiliary Devices

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

**UL 60947-5-1, 4th Ed., Issue Date: 2022-05-31, UL 60947-1,
Edition 6, Issue Date 2022-05-31**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L252354-131-82119002-7
Report reference E252354-20091128
Date 2024-04-02

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BA4	Contacts modules, open type
BX4	Contacts modules, open type
BX4-CA	Contacts modules, open type
CA4, followed by -04, -13, -22, -31 or -40, may be followed by E, M, N or U, followed by S.	Contacts modules, front mounted, four poles, open type
CA4 -, followed by 02, 11 or 20	Auxiliary Devices
CA4 followed by -04, -13, -22, -31, or -40, may be, followed by E, M, N or U followed by K.	Front mounted, four poles
CA4-01, , may be followed by -T.	Contacts modules, front mounted, one pole, open type
CA4-01K	Front mounted, one pole
CA4-01S	Contacts modules, front mounted, one pole, open type
CA4-04, may be followed by E, M, N, U or SP	Contacts modules, front mounted, four poles, open type
CA4-10, , may be followed by -T.	Contacts modules, front mounted, one pole, open type
CA4-10K	Front mounted, one pole
CA4-10S	Contacts modules, front mounted, one pole, open type
CA4-13, may be followed by E, M, N, U or SP	Contacts modules, front mounted, four poles, open type
CA4-22, may be followed by E, M, N, U or SP	Contacts modules, front mounted, four poles, open type
CA4-31, may be followed by E, M, N, U or SP	Contacts modules, front mounted, four poles, open type
CA4-40, may be followed by E, M, N, U or SP	Contacts modules, front mounted, four poles, open type
CAL-11KT	Contacts modules, lateral mounted, two poles, open type
CAL4-11	Contacts modules, lateral mounted, two poles, open type
CAL4-11K	Lateral mounted, two poles
CAL4-11S	Contacts modules, lateral mounted, two poles, open type
CAL4-11ST	Contacts modules, lateral mounted, two poles, open type



David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L252354-131-82119002-7
Report reference E252354-20091128
Date 2024-04-02

CAL4-11T	Contacts modules, lateral mounted, two poles, open type
CAT4-11	Contacts modules, front mounted, two poles, open type
CAT4-11E	Contacts modules, front mounted, two poles, open type
CAT4-11ES	Contacts modules, front mounted, two poles, open type
CAT4-11M	Contacts modules, front mounted, two poles, open type
CAT4-11MS	Contacts modules, front mounted, two poles, open type
CAT4-11MU	Contacts modules, front mounted, two poles, open type
CAT4-11S	Contacts modules, front mounted, two poles, open type
CAT4-11US	Contacts modules, front mounted, two poles, open type
CC4-01	Contacts modules, front mounted, one pole, open type
CC4-01K	Front mounted, one pole
CC4-01S	Contacts modules, front mounted, one pole, open type
CC4-01ST	Contacts modules, front mounted, one pole, open type
CC4-01T	Contacts modules, front mounted, one pole, open type
CC4-10	Contacts modules, front mounted, one pole, open type
CC4-10K	Front mounted, one pole
CC4-10S	Contacts modules, front mounted, one pole, open type
CC4-10ST	Contacts modules, front mounted, one pole, open type
CC4-10T	Contacts modules, front mounted, one pole, open type
Front mounted, one pole Cat. No. H04N, followed by -FL, followed by -01 or -10.	Auxiliary Devices
H04N-F, Cat. No. H04N, followed by -F, followed by -01 or -10.	Auxiliary Devices
H04N-L, Cat. No. H04N, followed by -L, followed by -11.	Auxiliary Devices


 David Piecuch
 UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.