

## 2C-0404: Wall plate horizontal 1/2"X1/2"



### Commercial information

Wallplate horizontal 1/2"x1/2"

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 49 mm    |
| Length     | 32 mm    |
| Width      | 49 mm    |
| Net weight | 0.093 kg |

#### Certificates

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

|                                    |                                                |                                  |                        |
|------------------------------------|------------------------------------------------|----------------------------------|------------------------|
| Material connection 1              | Brass                                          | Bend radius                      | 0 Millimetre           |
| Material quality connection 1      | CuZn40Pb2 (CW617N)                             | Length                           | 32 Millimetre          |
| Surface protection connection 1    | Untreated                                      | Wrench width                     | 0 Millimetre           |
| Surface treatment connection 1     | Untreated                                      | Wrench width union nut           | 0 Millimetre           |
| Material connection 2              | Brass                                          | Tightening torque                | 0 0 Newtonmetre        |
| Material quality connection 2      | CuZn40Pb2 (CW617N)                             | Medium temperature (continuous)  | -10 60 Degrees celsius |
| Surface protection connection 2    | Untreated                                      | Max. operating pressure at 20 °C | 10 Bar                 |
| Surface treatment connection 2     | Untreated                                      | Standard Dimension Ratio (SDR)   | 0                      |
| Reducing                           | ✗                                              |                                  |                        |
| Eccentric                          | ✗                                              |                                  |                        |
| System specific                    | ✓                                              |                                  |                        |
| Nominal diameter connection 1      | 1/2 inch (15)                                  |                                  |                        |
| Connection 1                       | Internal thread cylindrical BSPP-G (ISO 228-1) |                                  |                        |
| Nominal diameter connection 2      | 1/2 inch (15)                                  |                                  |                        |
| Connection 2                       | Internal thread cylindrical BSPP-G (ISO 228-1) |                                  |                        |
| Main colour fitting                | Brass                                          |                                  |                        |
| With buffer stud                   | ✓                                              |                                  |                        |
| High tensile strength              | ✗                                              |                                  |                        |
| With thermal insulation            | ✗                                              |                                  |                        |
| With sealing rings/gaskets         | ✓                                              |                                  |                        |
| Capped                             | ✗                                              |                                  |                        |
| With connection indicator          | ✗                                              |                                  |                        |
| With drain valve                   | ✗                                              |                                  |                        |
| With de-aerator                    | ✗                                              |                                  |                        |
| FM quality mark                    | ✗                                              |                                  |                        |
| LPCB quality mark                  | ✗                                              |                                  |                        |
| ULC quality mark                   | ✗                                              |                                  |                        |
| UL quality mark                    | ✗                                              |                                  |                        |
| DIN-CERTCO certificate             | ✗                                              |                                  |                        |
| VdS quality mark                   | ✗                                              |                                  |                        |
| With approval for TÜV              | ✗                                              |                                  |                        |
| DVGW quality mark for gas          | ✗                                              |                                  |                        |
| DVGW quality mark for water        | ✗                                              |                                  |                        |
| KIWA certified                     | ✗                                              |                                  |                        |
| Gastec QA mark                     | ✗                                              |                                  |                        |
| KOMO certified                     | ✗                                              |                                  |                        |
| Type approval according to BBR/EKS | ✗                                              |                                  |                        |