

START Downlight Flat IP44 Dimmable 205mm Round Recessed

START Downlight Flat 205 IP44 2250LM 840 DIM
0054125



Product features

- START Downlight Flat IP44 DIM is an integrated LED recessed downlight with a separate phase dimmable driver and loop in out box; 24W; 2250Lm; 94Lm/W; 4000K; IP44 rated from the front.



PRODUCT OVERVIEW


Product name	START Downlight Flat 205 IP44 2250LM 840 DIM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality
ETIM Class	EC001744
E-number FI	4278502
Warranty	5 years
Useful luminous flux (Fuse)	2250
Fixture luminous flux (lm)	2250
Luminaire efficacy (lm/W)	94
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	24
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK06
Product EAN number	5410288541259

PHOTOMETRY

START Downlight Flat IP44 Dimmable 205mm Round Recessed

START Downlight Flat 205 IP44 2250LM 840 DIM
0054125

0.5	1.44	E(0°) E(C0)	3211 308
1.0	2.88	E(0°) E(C0)	1605 154
1.5	4.32	E(0°) E(C0)	1070 103
2.0	5.76	E(0°) E(C0)	803 77
2.5	7.19	E(0°) E(C0)	642 62
3.0	8.63	E(0°) E(C0)	535 51
Distance [m] Cone diameter [m]		Illuminance [lx]	
C0 - C180 (Half beam angle: 110.4°)			



TECHNICAL DRAWINGS

