



### Features

- Pixo Line is a linear track system, adds flexibility to any space due the variety of product options Offers an easy installation with two separate modules Push-in/push-out mechanism with GR6d-15 connector Compatible with Zhaga Book 14 Aluminium body, plastic end caps,aluminised plastic low glare optics in a single line configuration, light beam angle:70° Textured white finishing colour. Light color temperature: 3000K, warm white, max. system power: 50W Max. fixture lumen output: 7300lm, efficacy: 146lm/W, Ra80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), IR/UV free light source without heat radiation Multipower driver module with 8 power settings meet all installation needs with one single product (selection between 17W, 19W, 24W, 29W, 34W, 38W, 43W, 50W)Suitable for 3-circuit tracks, Electrical protection: Class III. Degree of protection: IP20, suitable for indoor environment only Light modules should be combined with suitable in-track drivers Nominal product dimensions: L.1464mmx37.4mmx37mm


### Product Overview

Product name	PIXO LINE 1500 UGR19 830 WHITE
Technology	LED
Cap/Base	N/A
General application	Retail, Hospitality, Museums & Galleries, Office
ETIM Class	EC000996
E-number FI	4279409
Fixture luminous flux (lm)	7300
Luminaire efficacy (lm/W)	146
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3

## PIXO LINE 1500 UGR19 830 WHITE 0007825

Beam Angle (°)	70
Glare control	< 19
Photobiological Risk Group	Not applicable
Total power consumption (W)	50
Electrical protection	Class III
Dimmable	No
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5410288078250
Warranty	5 years
Dimming method	N/A

### Photometry



### Technical drawings

