

Product features





PRODUCT OVERVIEW

Product name	Pigmy Oven lamp 15w 22mm 230-240V SLV
Technology	Incandescent
Watt (Rated) (W)	15
Lamp shape	Other
Туре	Pygmy Clear
Cap/Base	E14
Lamp finish	Clear
Fixture rating	Open
General application	Hospitality, Residential & Consumer, Retail
ETIM Class	EC000014
E-number FI	4741158
Warranty	2 years
Luminous flux (Im)	110
Colour temperature (K)	2500
Light colour	Homelight
CRI (Ra)	100
Colour Variation Initial (SDCM)	N/A
Photobiological Risk Group	Not applicable
Wattage (W)	15
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Average life (Nominal) (h)	1000
Product EAN number	5410288080741

DATA TABLE

General data	
Product name	Pigmy Oven lamp 15w 22mm 230-240V SLV
Technology	Incandescent
Watt (Rated) (W)	15
Lamp shape	Other
Туре	Pygmy Clear
Cap/Base	E14
Lamp finish	Clear



Fixture rating
ETIM Class
E-number FI
Optical data Luminous flux (Im) 110 Luminous flux (Rated) (Im) 90 Colour temperature (K) 2500 Light colour Homelight CRI (Ra) 100 Colour Variation Initial (SDCM) N/A Adjustable chromaticity N Photobiological Risk Group Not applicable Electrical data Wattage (W) 15 Starting time (max) (s) 0.01 Warm-up time to 60% of full light (max) (s) Primary Supply/Product voltage - min (V) Primary Supply/Product voltage - max (V) Lamp power factor 1 Control gear required No. Of switching cycles before premature failures Dimmable Yes Dimmable Yes Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Length (mm) 48 Nominal Product Length (mm) - C/L 49 Max. Lamp Lamp Lamp Lame (mm) - C/L 49 Max. Lamp Dalmeter (mm) - D 23
Optical data Luminous flux (Im) 110 Luminous flux (Rated) (Im) 90 Colour temperature (K) 2500 Light colour Homelight CRI (Ra) 100 Colour Variation Initial (SDCM) N/A Adjustable chromaticity N Photobiological Risk Group Not applicable Electrical data Wattage (W) 15 Starting time (max) (s) 0.01 Warm-up time to 60% of full light (max) (s) Primary Supply/Product voltage - min (V) Primary Supply/Product voltage - max (V) Lamp power factor 1 Control gear required No No. Of switching cycles before premature fallures Dimmable Yes Dimmable Yes Dimmable Yes Dimmable (Lass) G KWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Length (mm) - C/L 49 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Luminous flux (Im) 110 Luminous flux (Rated) (Im) 90 Colour temperature (K) 2500 Light colour Homelight CRI (Ra) 100 Colour Variation Initial (SDCM) N/A Adjustable chromaticity N Photobiological Risk Group Not applicable Electrical data Wattage (W) 15 Starting time (max) (s) 0.01 Warm-up time to 60% of full light (max) (s) Primary Supply/Product voltage - min (V) 230 Primary Supply/Product voltage - min (V) 240 Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Luminous flux (Rated) (Im) 90 Colour temperature (K) 2500 Light colour Homelight CRI (Ra) 100 Colour Variation Initial (SDCM) N/A Adjustable chromaticity N Photobiological Risk Group Not applicable Electrical data Wattage (W) 15 Starting time (max) (s) 0.01 Warm-up time to 60% of full light (max) (s) Primary Supply/Product voltage - min (V) 230 Primary Supply/Product voltage - max (V) Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G KWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Luminous flux (Rated) (Im) 90 Colour temperature (K) 2500 Light colour Homelight CRI (Ra) 100 Colour Variation Initial (SDCM) N/A Adjustable chromaticity N Photobiological Risk Group Not applicable Electrical data Wattage (W) 15 Starting time (max) (s) 0.01 Warm-up time to 60% of full light (max) (s) Primary Supply/Product voltage - min (V) 230 Primary Supply/Product voltage - max (V) Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Length (mm) - C/L Max. Lamp Diameter (mm) - D 23
Colour temperature (K) 2500 Light colour Homelight CRI (Ra) 100 Colour Variation Initial (SDCM) N/A Adjustable chromaticity N Photobiological Risk Group Not applicable Electrical data Wattage (W) 15 Starting time (max) (s) 0.01 Warm-up time to 60% of full light (max) (s) Primary Supply/Product voltage - min (V) 230 Primary Supply/Product voltage - min (V) Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimming method Mains: leading / trailling edge Lamp Energy Label (class) G KWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Light colour CRI (Ra) 100 Colour Variation Initial (SDCM) N/A Adjustable chromaticity N Photobiological Risk Group Not applicable Electrical data Wattage (W) 15 Starting time (max) (s) 0.01 Warm-up time to 60% of full light (max) (s) Primary Supply/Product voltage - min (V) 230 Primary Supply/Product voltage - max (V) Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D
CRI (Ra) 100 Colour Variation Initial (SDCM) N/A Adjustable chromaticity N Photobiological Risk Group Not applicable Electrical data Wattage (W) 15 Starting time (max) (s) 0.01 Warm-up time to 60% of full light (max) (s) Instant full light (s) Primary Supply/Product voltage - min (V) 230 Primary Supply/Product voltage - max (V) Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G KWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Length (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Colour Variation Initial (SDCM) Adjustable chromaticity Photobiological Risk Group Not applicable Electrical data Wattage (W) Starting time (max) (s) Warm-up time to 60% of full light (max) (s) Primary Supply/Product voltage - min (V) Primary Supply/Product voltage - min (V) Lamp power factor Control gear required No No. Of switching cycles before premature failures Dimmable Ves Dimming method Lamp Energy Label (class) KWh per 1000 hours burning time Average life (Nominal) (h) Average life (Rated) (h) Nominal Product Length (mm) Nominal Product Length (mm) Nominal Product Diameter (mm) Max. Lamp Length (mm) - C/L Max. Lamp Length (mm) - C/L Max. Lamp Diameter (mm) - D 25 Both Not applicable 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) Average life (Rated) (h) Average life (Rated) (h) Average life (Rated) (mm) Average life (Rated) (mm) Average life (Rated) (mm) Average life (mm) - C/L Averag
Adjustable chromaticity Photobiological Risk Group Not applicable Electrical data Wattage (W) 15 Starting time (max) (s) 0.01 Warm-up time to 60% of full light (max) (s) Primary Supply/Product voltage - min (V) Primary Supply/Product voltage - max (V) Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L Max. Lamp Length (mm) - C/L Max. Lamp Length (mm) - D 23
Electrical data Wattage (W) 15 Starting time (max) (s) 0.01 Warm-up time to 60% of full light (max) (s) Instant full light (s) Primary Supply/Product voltage - min (V) 230 Primary Supply/Product voltage - max (V) Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Electrical data Wattage (W) 15 Starting time (max) (s) 0.01 Warm-up time to 60% of full light (max) (s) Instant full light (s) Primary Supply/Product voltage - min (V) 230 Primary Supply/Product voltage - max 240 (V) Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Length (mm) 48 Nominal Product Length (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Wattage (W) 15 Starting time (max) (s) 0.01 Warm-up time to 60% of full light (max) (s) Primary Supply/Product voltage - min (V) 230 Primary Supply/Product voltage - max (V) Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Starting time (max) (s) Warm-up time to 60% of full light (max) (s) Primary Supply/Product voltage - min (V) Primary Supply/Product voltage - max (V) Lamp power factor Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimmable Yes Dimming method Lamp Energy Label (class) KWh per 1000 hours burning time Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Loimeter (mm) Max. Lamp Length (mm) - C/L Max. Lamp Diameter (mm) - D 230 Instant full light Instant full li
Starting time (max) (s) Warm-up time to 60% of full light (max) (s) Primary Supply/Product voltage - min (V) Primary Supply/Product voltage - max (V) Lamp power factor Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimmable Yes Dimming method Lamp Energy Label (class) KWh per 1000 hours burning time Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Loimeter (mm) Max. Lamp Length (mm) - C/L Max. Lamp Diameter (mm) - D 230 Instant full light Instant full li
Warm-up time to 60% of full light (max) (s) Primary Supply/Product voltage - min (V) 230 Primary Supply/Product voltage - max (V) Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
rimary Supply/Product voltage - min (V) 230 Primary Supply/Product voltage - max (V) Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Primary Supply/Product voltage - max (V) Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
(V) Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Lamp power factor 1 Control gear required No No. Of switching cycles before premature failures Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Control gear required No. Of switching cycles before premature failures Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) KWh per 1000 hours burning time Lifetime data Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Max. Lamp Length (mm) - C/L Max. Lamp Diameter (mm) - D 23
No. Of switching cycles before premature failures Dimmable Yes Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
failures Dimmable Dimming method Lamp Energy Label (class) KWh per 1000 hours burning time Lifetime data Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Max. Lamp Length (mm) - C/L Max. Lamp Diameter (mm) - D Yes Mains: leading / trailing edge 15 15 1000 Auins: leading / trailing edge 15 1000 48 48 48 48 48 48 48 48 48
Dimming method Mains: leading / trailing edge Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Lamp Energy Label (class) G kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
kWh per 1000 hours burning time 15 Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Lifetime data Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Average life (Nominal) (h) 1000 Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Average life (Rated) (h) 1000 Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Physical data Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Nominal Product Length (mm) 48 Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Nominal Product Diameter (mm) 22 Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Max. Lamp Length (mm) - C/L 49 Max. Lamp Diameter (mm) - D 23
Max. Lamp Diameter (mm) - D 23
W L L ()
Weight (kg) 0.009
Dealersing
Packaging
Single packaging type Carton
Product EAN number 5410288080741
Packaging single length / height (cm) 9.0
Packaging single length / height (cm) 9.0 Packaging single width (cm) 5.0 Packaging single depth (cm) 2.5




DUN14 (outer)	15410288080748
Units per outer package	14
Packaging outer length / height (cm)	12.8
Packaging outer width (cm)	19.0
Packaging outer depth (cm)	10.0

Safety data

Breakage cleaning instructions	Not applicable
Recommendation for disposal at end of life	Not Applicable
Special purpose lamp	Yes
Suitable for household illumination	No
Safety message	Not suitable for household

PHOTOMETRY



TECHNICAL DRAWINGS



