



### Features

- Pixo Line is a linear track system, adds flexibility to any space due the variety of product options Offers an easy installation with two separate modules Push-in/push-out mechanism with GR6d-15 connector Compatible with Zhaga Book 14 Aluminium body, plastic end caps, traslucent asymmetric optic diffuser, light beam angle:25° white finishing colour. Light color temperature: 4000K, max. system power: 50W Max. fixture lumen output: 7400lm, efficacy: 148lm/W, Ra80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), IR/UV free light source without heat radiation Multipower driver module with 8 power settings meet all installation needs with one single product (selection between 17W, 19W, 24W, 29W, 34W, 38W, 43W, 50W) Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack Electrical protection: Class III. Degree of protection: IP20, suitable for indoor environment only Light modules should be combined with suitable in-track drivers Nominal product dimensions: L.1464mmx38.4mmx37mm


### Product Overview

Product name	PIXO LINE 1500 ASYM R 840 WHITE
Technology	LED
Cap/Base	N/A
General application	Retail, Hospitality, Museums & Galleries, Office
ETIM Class	EC000996
Fixture luminous flux (lm)	7400
Luminaire efficacy (lm/W)	148
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80


## PIXO LINE 1500 ASYM R 840 WHITE 0007836

Colour Variation Initial (SDCM)	3
Beam Angle (°)	90
Beam Angle (°)	Single assymmetric 25right
Photobiological Risk Group	Not applicable
Total power consumption (W)	50
Electrical protection	Class III
Dimmable	No
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5410288078366
Warranty	5 years
Dimming method	N/A


### Photometry



## PIXO LINE 1500 ASYM R 840 WHITE 0007836



### Technical drawings



### Data table

## PIXO LINE 1500 ASYM R 840 WHITE 0007836

### GENERAL DATA

Product name	PIXO LINE 1500 ASYM R 840 WHITE
Technology	LED
Cap/Base	N/A
General application	Retail, Hospitality, Museums & Galleries, Office
Operating temperature range (°C)	-20°C...+40°C
ETIM Class	EC000996
Warranty	5 years

### OPTICAL DATA

Fixture luminous flux (lm)	7400
Luminaire efficacy (lm/W)	148
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	90
Beam Angle (°)	Single assymetric 25right
Photobiological Risk Group	Not applicable

### ELECTRICAL DATA

Total power consumption (W)	50
Electrical protection	Class III
Control gear required	No
Dimmable	No
Dimming method	N/A
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	N/A

### LIFETIME DATA

Lifespan L70 B50	90000
------------------	-------

## PIXO LINE 1500 ASYM R 840 WHITE 0007836

Lifespan L70 B20	90000
Lifespan L70 B10	90000
Lifespan L80 B50	90000
Lifespan L80 B20	79000
Lifespan L80 B10	76000
Lifespan L90 B50	43000
Lifespan L90 B20	37000
Lifespan L90 B10	36000

### PHYSICAL DATA

Housing colour	White
IP rating	IP20
IK rating	IK03
Nominal Product Length (mm)	1464
Nominal Product Width (mm)	37
Nominal Product Height (mm)	38.4
Weight (kg)	0.9

### PACKAGING

Product EAN number	5410288078366
Packaging single length / height (cm)	147.0
Packaging single width (cm)	4.3
Packaging single depth (cm)	4.3
DUN14 (outer)	15410288078363
Units per outer package	20
Packaging outer length / height (cm)	149.0
Packaging outer width (cm)	24.0
Packaging outer depth (cm)	19.0

### SAFETY DATA

Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No

**SYLVANIA**

PIXO LINE 1500 ASYM R 840 WHITE  
**0007836**

---



**Light your world**