

FICHE TECHNIQUE DU PRODUIT

Type: SM-Dimm-X3-ARC-NA
Art. Nr.: 9300212



Brève description

SOLAMAGIC ARC sans fil émetteurs de variateur 3 positions à 3kW Nano-A



*** Image missing:
 /Data/Environments/000039/Attachment/Bijlage/PRD/4026911000003/PHI/SOLAMAGIC-DM-NA.tif ***

Description du produit

Les radiateurs peuvent être gradés à 3kW avec le module de gradation sans fil SOLAMAGIC ARC. Le module est monté sur le radiateur par montage rapide. L'émetteur portatif sans fil à 4 canaux est requis comme accessoire. Le module de gradation est disponible dans les couleurs suivantes: blanc, titane ou nano-anthracite, type de protection: IP 44, dimensions: 115 x 92 x 200 mm, fréquence radio: 433 mHz, portée: 20 m.

Caractéristiques de l'ETIM

Assembly arrangement	Basic element with complete housing	Number of modules (module system)	1
Method of operation	Radio frequency (RF)	Number of units	1
App control via Bluetooth	✗	RAL-number (similar)	7016
Dimming phase cut-on (leading edge)	✓	Nominal voltage	230 230 Volt
Dimming phase cut-off (trailing edge)	✗	Frequency	50 50 Hertz
Serial dimmer	✗	Control voltage	230 230 Volt
Type of load	Universal	Nominal power resistive load	3000 3000 Watt
Substation input	✗	Nominal power inductive load	16 16 Voltampere
Light value memory	✗	Nominal power capacitive load	5 5 Voltampere
Applicable with button	✗	Max. switching power LED	0 Watt
Applicable with movement sensor	✗	Power consumption	3,5 Watt
Applicable with presence indicator	✗	Core cross section	1,5 1,5 Square millimetre
Applicable with time switch/timer	✗	Device width	115 Millimetre
Applicable with transmission button	✓	Device height	200 Millimetre
Applicable with infrared button	✗	Device depth	92 Millimetre
Mounting method	Surface mounted	Min. depth of built-in installation box	0 Millimetre
Type of fastening	Mounting with screw		
Material	Metal		
Material quality	Aluminium		
Halogen free	✗		
Surface protection	Anodised		
Surface finishing	Glossy		
Colour	Anthracite		

Créé le: 09/10/2024

FICHE TECHNIQUE DU PRODUIT

Transparent	×
Suitable for degree of protection (IP)	IP44
Impact strength	IK03
Connection type	Other
Compatible with Apple HomeKit	×
Compatible with Google Assistant	×
Compatible with Amazon Alexa	×
IFTTT support available	×

Cr    le: 09/10/2024