



### Features

- Pixo Line is a linear track system, adds flexibility to any space due the variety of product options Offers an easy installation with two separate modules Push-in/push-out mechanism with GR6d-15 connector Compatible with Zhaga Book 14 Constant current 350mA -1050mA digital dimmable DALI in-track driver with GR6d-15 connector for LED light modules, polycarbonate body Clip holder and fixing screw included in the driver box, white finishing colour, max. system power: 56W, operating voltage: 220-240V / 50-60Hz Driver module should be combined with suitable LED module. Switch-dim selection with 8 power settings meet all installation needs with one single product (selection between 17W, 19W, 24W, 29W, 34W, 38W, 43W, 50W) Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack Electrical protection: Class I. Degree of protection: IP20, suitable for indoor environment only Light modules should be combined with suitable in-track drivers Nominal product dimensions: L.672mmx32mmx31mm



### Product Overview

<b>Product name</b>	PIXO LINE DRIVER DALI 600 WHITE
<b>Technology</b>	LED
<b>General application</b>	Retail, Hospitality, Museums & Galleries, Office
<b>ETIM Class</b>	EC002710
<b>Light colour</b>	N/A
<b>Photobiological Risk Group</b>	Not applicable
<b>Total power consumption (W)</b>	56
<b>Electrical protection</b>	Class I
<b>Dimmable</b>	Yes
<b>LED Flickering Rate</b>	Ultra low (5% or less)
<b>Housing colour</b>	White

## PIXO LINE DRIVER DALI 600 WHITE 0007867

IP rating	IP20
IK rating	IK03
Product EAN number	5410288078670
Warranty	5 years
Dimming method	DALI

### Technical drawings

