

Optix Surface 1200 Direct - Indirect High Output SylSmart
OPTIX SURFACE 1200x200 2 LINE D/I HO 4000K ALU SSC
2023749




PRODUCT OVERVIEW

Product name	OPTIX SURFACE 1200x200 2 LINE D/I HO 4000K ALU SSC
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Suspended
Fixture rating	Enclosed
Warranty	5 years
Fixture luminous flux (lm)	5600
Luminaire efficacy (lm/W)	151
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 16
Photobiological Risk Group	RG1
Total power consumption (W)	37
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768237494

PHOTOMETRY

Optix Surface 1200 Direct - Indirect High Output SylSmart
OPTIX SURFACE 1200x200 2 LINE D/I HO 4000K ALU SSC
 2023749



TECHNICAL DRAWINGS

