

# Concord

## NILO 1200 DIR/INDIR 3K DALI WHITE 2050608



### Features

- Nilo is a 360° curve-shaped luminaire with a striking, minimalistic design, perfect for retail, hospitality, and office environments. The product can be suspended at different heights to create appealing lighting effects. Stand-alone and self-contained lighting fixture. Aluminium body, opal diffuser, emits direct and indirect lighting. Textured white finishing colour. Light color temperature: 3000K, warm white. System power: 85W. Fixture lumen output: 9120lm, efficacy: 107lm/W, Ra80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), IR/UV free light source without heat radiation. DALI dimmable, 220-240V / 50-60Hz. 75% direct, and 25% indirect lighting. Electrical protection: Class I. Degree of protection: IP20, suitable for indoor environment only. Nominal product dimensions: diameter 1140mmx65mm.

### Product Overview


Product name	NILO 1200 DIR/INDIR 3K DALI WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
General application	Hospitality, Retail, Museums & Galleries
ETIM Class	EC002892
Fixture luminous flux (lm)	9120
Luminaire efficacy (lm/W)	107
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 23

# Concord

## NILO 1200 DIR/INDIR 3K DALI WHITE 2050608

Photobiological Risk Group	RG0
Total power consumption (W)	85
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5025768506088
Warranty	5 years
Dimming method	DALI

### Photometry



### Technical drawings

