


Walraven RapidStrut® Rail Connector G2 (BUP1000)

(H2874)

to make Strut rail fabrications



Features & benefits

- connector with pre-assembled Walraven RapidStrut® Slide nut(s)
- to make fabrication with Walraven RapidStrut® Rail
- ready-to-use pre-assembled for a quick fixing, and retains assembly in place before final tightening
- 'Direct Twist' technology for easy and secure installation
- visual guide to check the position of the slide nut
- optimized for easy installation with electrical tools
- material: metal parts made of steel 1.0332; spring(s) made of POM (polyoxymethylene), green
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227

Product Number	VVS Number	For Rail Type	Total Height	Total Width	Total Length	Material Thickness	Heart To Heart Distance	Torque Moment For Installation
<i>Reference letter</i>			<i>H</i>	<i>W</i>	<i>L</i>	<i>MT</i>	<i>k</i>	<i>T_{inst.}</i>
<i>Unit description</i>			<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>Nm</i>
665885184	018047132	41x21, 41x41, 41x51, 41x62, 41x82	31.4	40	82	4.00	41	30
665885186	018047135	41x21, 41x41, 41x51, 41x62, 41x82	31.4	40	164	4.00	41	30