

## Resisto fixed output

Resisto 600 IP66 1600lm 865  
0010204



### Product features

- Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 1600lm; 12W; 133lm/W; 6500K; SDCM<5; non dimmable; CRI80; IP66; IK08; Class I; 69,000hrs (L80B20) lifespan; 650mm x 89mm x 88mm; D-mark.




### PRODUCT OVERVIEW

|                                 |   |
|---------------------------------|---|
| Product name                    | Resisto 600 IP66 1600lm 865                               |
| Technology                      | LED   |
| Cap/Base                        | N/A   |
| Housing                         | PC Polycarbonate  |
| Mount                           | Ceiling surface mounting, Suspended, Wall surface mounted |
| General application             | Logistics & Industry                                      |
| ETIM Class                      | EC002892  |
| E-number FI                     | 4357038   |
| Warranty                        | 5 years   |
| Fixture luminous flux (lm)      | 1600  |
| Luminaire efficacy (lm/W)       | 133   |
| Colour temperature (K)          | 6500  |
| CRI (Ra)                        | 80  |
| Colour Consistency (SDCM)       | 5   |
| Colour Variation Initial (SDCM) | SDCM5   |
| Beam Angle (°)                  | 110   |
| Glare control                   | < 22  |
| Photobiological Risk Group      | RG1   |
| Total power consumption (W)     | 12  |
| Electrical protection           | Class I   |
| Control gear type               | LED driver constant current                               |
| Dimmable                        | No  |
| Dimming method                  | N/A   |
| LED Flickering Rate             | Low (6% - 20%)  |
| Housing colour                  | Grey  |
| IP rating                       | IP66  |
| IK rating                       | IK08  |
| Product EAN number              | 5410288102047   |

### PHOTOMETRY

## Resisto fixed output

Resisto 600 IP66 1600lm 865  
0010204



## TECHNICAL DRAWINGS

