

# Product data sheet Spirotech

## Product name

**EVU Expansion vessel 10bar 240L, standing**

## Product properties

EVU-10 Universal expansion vessels with replaceable membrane, P max. 10 bar / T max. 70°C.  
Expansion vessels larger than 300 liters on request.

- Tested according to Pressure Equipment Directive 2014/68/EU
- Max. temperature at connection point: 70 degrees
- Max. operating pressure: 10 bar

## Article number

**EVU240-10**

## Product image



## Product dimensions

# Product data sheet Spirotech

## ETIM product data

|                                       |                                                       |
|---------------------------------------|-------------------------------------------------------|
| Height                                | 1195 mm                                               |
| Volume                                | 240 l                                                 |
| Colour                                | Other                                                 |
| Diameter                              | 600 mm                                                |
| Max. operating pressure               | 10 bar                                                |
| Connection                            | External thread conical BSPT-R (ISO 7-1 / EN 10226-1) |
| With pressure gauge                   | No                                                    |
| With exchangeable membrane            | Yes                                                   |
| Nominal diameter expansion connection | 1 inch (25)                                           |
| Horizontal positioning                | No                                                    |
| Suitable for central heating          | Yes                                                   |
| Vertical positioning                  | Yes                                                   |

|                                      |                                                |
|--------------------------------------|------------------------------------------------|
| With legs                            | Yes                                            |
| Material membrane/bladder            | Ethylene-propylene diene monomer rubber (EPDM) |
| With drain                           | No                                             |
| With safety valve                    | No                                             |
| With mounting material               | No                                             |
| Max. glycol mixture                  | 60 %                                           |
| Suitable for tap water               | No                                             |
| Max. ethanol mixture                 | 60 %                                           |
| Suitable for solar collector circuit | Yes                                            |
| Pre-pressure                         | 3.5 bar                                        |
| With fixed wall support              | No                                             |
| Suitable for cooling                 | Yes                                            |

### Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website

