

Threefold faceplate, horizontal 71 mm centre distance, for one 45x45 function, a double and a single switch function, Niko Toggle brass dark bronze patina

211-57722

4 year
warranty

The Niko Toggle threefold horizontally oriented faceplate clicks onto one 45x45 function, a double and a single switch function that have been horizontally installed next to each other with a centre distance of 71 mm. The faceplate combines with any available Niko 45 x 45 mm finishing set and Niko Toggle for single and double switch functions. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upperframe is made of brass. The lower frame is made of anthracite polycarbonate (PC) + acrylic-styrene-acrylate (ASA). The lead concentration in the brass is higher than 0.1% (w/w). The upper frame is 6 mm thick and the lower frame 2 mm.



Niko recommends a design combination with a finishing set in the following colour: brass dark bronze patina for Niko Rocker and Niko Toggle finishing sets and dark brown coated for other finishing sets.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)
- Designed to fit any available 45 x 45 mm function

Technical data

Threefold faceplate, horizontal 71 mm centre distance, for one 45x45 function, a double and a single switch function, Niko Toggle brass dark bronze patina.

- Number of spaces for mechanisms: 3
- Colour faceplate: brass dark bronze patina
- Colour RAL (approximately): 060 40 10
- Colour NCS (approximately): NCS S 7005-Y50R
- Recommended colour central plate: brass dark bronze patina for Niko Rocker and Niko Toggle finishing sets and dark brown coated for other finishing sets
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.

- Material finishing: The upperframe is made of brass. The lower frame is made of anthracite polycarbonate (PC) + acrylic-styrene-acrylate (ASA). The lead concentration in the brass is higher than 0.1% (w/w).
- Surface treatment: patina and protective varnish
- Surface finishing: matt
- Coating upper frame: the upperframe is enamelled bronze
- Coating lower frame: enamelled dark brown
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Surface-mounting height: max. 8.5 mm
- Fire safety:
 - self-extinguishing: complies with a filament test of 650°C
- Centre-to-centre distance: 71 mm
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP20D
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 mm x 225 mm x 13 mm
- Dimensions visible (HxWxD): 83 mm x 225 mm