




Color:  gray/green-yellow

Similar to illustration

Female connector, 2020 Series, gray/green-yellow

Enjoy easy electrical installations with this female connector (item number 2020-210/000-036). Ensure that the strip lengths are between 9 and 11 mm when connecting conductors to this female connector. Pluggable rail-mount terminal blocks are primarily found in switchgear units and control systems, most notably in railroad technology. These innovative systems combine the benefits of rail-mount terminal blocks and connectors for a flexible and reliable wiring system. You also have the option of pre-assembling installations, which not only makes production but also installation, operation, and maintenance more efficient and cost-effective. This product incorporates conductor terminals and utilizes Push-in CAGE CLAMP®. Push-in CAGE CLAMP® technology provides a universal connection solution for all conductor types. It allows both solid and fine-stranded conductors with ferrules to be inserted directly into the clamping point without the need for tools. The dimensions are (35.7 x 40.5 x 25) mm (width x height x depth). This female connector is suitable for conductor cross sections ranging from 0.14 mm² to 1.5 mm².

This female connector/socket is operated with an operating tool.

| Notes                |                                                                                                                                         |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Safety Information   | According to EN 61984, pluggable connectors without current interrupting capacity must not be mated or unmated when live or under load. |
| Safety information 2 | Notice: An appropriate end plate must be applied to the carrier terminal blocks after each female plug.                                 |

| Electrical data                 |        |              |     |    |               |                   |
|---------------------------------|--------|--------------|-----|----|---------------|-------------------|
| Ratings per                     |        | IEC/EN 61984 |     |    | Approvals per |                   |
|                                 |        |              |     |    | UL 1059       |                   |
|                                 |        |              |     |    |               |                   |
| Overvoltage category            |        | III          | III | II | Use group     | B C D             |
| Pollution degree                |        | 3            | 2   | 2  | Rated voltage | 300 V 300 V 300 V |
| Nominal voltage                 | 500 V  | -            | -   | -  | Rated current | 15 A 15 A 15 A    |
| Rated impulse withstand voltage | 6 kV   | -            | -   | -  |               |                   |
| Rated current                   | 13.5 A | -            | -   | -  |               |                   |



| Approvals per |  | CSA 22.2 No 158 |       |       |
|---------------|--|-----------------|-------|-------|
| Use group     |  | B               | C     | D     |
| Rated voltage |  | 300 V           | 300 V | 300 V |
| Rated current |  | 10 A            | 10 A  | 10 A  |

| General information |                    |
|---------------------|--------------------|
| Wiring direction    | Front-entry wiring |

Connection Data

|                            |    |
|----------------------------|----|
| Clamping units             | 20 |
| Total number of potentials | 10 |

| Connection 1                                               |                                                                                                                                   |
|------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Connection technology                                      | Push-in CAGE CLAMP®                                                                                                               |
| Actuation type                                             | Operating tool                                                                                                                    |
| Connectable conductor materials                            | Copper                                                                                                                            |
| Nominal cross-section                                      | 1 mm²                                                                                                                             |
| Solid conductor                                            | 0.14 ... 1.5 mm² / 24 ... 16 AWG                                                                                                  |
| Solid conductor; push-in termination                       | 0.5 ... 1.5 mm² / 20 ... 16 AWG                                                                                                   |
| Fine-stranded conductor                                    | 0.14 ... 1.5 mm² / 24 ... 16 AWG                                                                                                  |
| Fine-stranded conductor; with insulated ferrule            | 0.14 ... 0.75 mm² / 24 ... 18 AWG                                                                                                 |
| Fine-stranded conductor; with ferrule; push-in termination | 0.5 ... 0.75 mm² / 20 ... 18 AWG                                                                                                  |
| Note (conductor cross-section)                             | Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination. |
| Strip length                                               | 9 ... 11 mm / 0.35 ... 0.43 inches                                                                                                |
| Pole number                                                | 10                                                                                                                                |
| Wiring direction                                           | Front-entry wiring                                                                                                                |

Physical data

|              |                        |
|--------------|------------------------|
| Width        | 35.7 mm / 1.406 inches |
| Height       | 40.5 mm / 1.594 inches |
| Depth        | 25 mm / 0.984 inches   |
| Module width | 3.5 mm / 0.138 inches  |

Mechanical data

|                          |              |
|--------------------------|--------------|
| Variable coding          | Yes          |
| Marking level            | Side marking |
| Anti-rotation protection | Yes          |

Plug-in connection

|                                    |                         |
|------------------------------------|-------------------------|
| Contact type (pluggable connector) | Female connector/socket |
| Connector (connection type)        | for conductor           |
| Mismating protection               | No                      |

Material data

|                                    |                                                                          |
|------------------------------------|--------------------------------------------------------------------------|
| Note (material data)               | <a href="#">Information on material specifications can be found here</a> |
| Color                              | gray/green-yellow                                                        |
| Material group                     | I                                                                        |
| Insulation material (main housing) | Polyamide (PA66)                                                         |
| Flammability class per UL94        | V0                                                                       |
| Fire load                          | 0.456 MJ                                                                 |
| Weight                             | 27.7 g                                                                   |



| Environmental requirements       |                 |
|----------------------------------|-----------------|
| Processing temperature           | -35 ... +85 °C  |
| Continuous operating temperature | -60 ... +105 °C |

| Commercial data       |                   |
|-----------------------|-------------------|
| Product Group         | 18 (X-COM-System) |
| PU (SPU)              | 25 pcs            |
| Packaging type        | Box               |
| Country of origin     | DE                |
| GTIN                  | 4050821221869     |
| Customs tariff number | 85366990990       |

| Product Classification |                      |
|------------------------|----------------------|
| UNSPSC                 | 39121409             |
| eCl@ss 10.0            | 27-14-11-06          |
| eCl@ss 9.0             | 27-14-11-06          |
| ETIM 9.0               | EC001284             |
| ETIM 10.0              | EC001284             |
| ECCN                   | NO US CLASSIFICATION |

| Environmental Product Compliance |                         |
|----------------------------------|-------------------------|
| RoHS Compliance Status           | Compliant, No Exemption |

| Approvals / Certificates                                                           |          |                                                            |
|------------------------------------------------------------------------------------|----------|------------------------------------------------------------|
| General approvals                                                                  |          | Declarations of conformity and manufacturer's declarations |
|  |          |                                                            |
| Approval                                                                           | Standard | Certificate Name                                           |
| CCA<br>DEKRA Certification B.V.                                                    | EN 60947 | NTR NL 7617                                                |
| UL<br>UL International Germany GmbH                                                | UL 1059  | E 45172                                                    |
| Approval                                                                           | Standard | Certificate Name                                           |
| EU-Declaration of Confor-<br>mity<br>WAGO GmbH & Co. KG                            | -        | -                                                          |
| UK-Declaration of Confor-<br>mity<br>WAGO GmbH & Co. KG                            | -        | -                                                          |

| Downloads                                               |                                                                                     |
|---------------------------------------------------------|-------------------------------------------------------------------------------------|
| Environmental Product Compliance                        |                                                                                     |
| Compliance Search                                       |                                                                                     |
| Environmental Product<br>Compliance<br>2020-210/000-036 |  |



Documentation

| Bid Text         |            |                  |  |
|------------------|------------|------------------|--|
| 2020-210/000-036 | 19.02.2019 | xml<br>4.01 KB   |  |
| 2020-210/000-036 | 07.08.2018 | docx<br>15.20 KB |  |

CAD/CAE-Data

| CAD data                         | CAE data                              |
|----------------------------------|---------------------------------------|
| 2D/3D Models<br>2020-210/000-036 | EPLAN Data Portal<br>2020-210/000-036 |
|                                  | WSCAD Universe<br>2020-210/000-036    |
|                                  | ZUKEN Portal<br>2020-210/000-036      |

1 Compatible Products

1.1 Optional Accessories

1.1.1 Ferrule

1.1.1.1 Ferrule



|                                                                                                                                                                                |                                                                                                                                                                                |                                                                                                                                                                            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Item No.: 216-241</b><br>Ferrule; Sleeve for 0.5 mm² / 20 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; white | <b>Item No.: 216-242</b><br>Ferrule; Sleeve for 0.75 mm² / 18 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; gray | <b>Item No.: 216-243</b><br>Ferrule; Sleeve for 1 mm² / AWG 18; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; red |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

1.1.2 Locking system

1.1.2.1 Locking system



|                                                  |                                                    |
|--------------------------------------------------|----------------------------------------------------|
| <b>Item No.: 2022-151</b><br>Locking lever; gray | <b>Item No.: 2022-152</b><br>Locking lever; orange |
|--------------------------------------------------|----------------------------------------------------|

1.1.3 Marking

1.1.3.1 Marker



|                                                                                    |                                                                                                             |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| <b>Item No.: 793-3501</b><br>WMB marking card; as card; plain; snap-on type; white | <b>Item No.: 2009-113</b><br>WMB-Inline; for Smart Printer; 2300 pieces on roll; plain; snap-on type; white |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|

1.1.4 Protective warning marker

1.1.4.1 Cover



**Item No.: 2000-115**  
Protective warning marker; for 5 terminal blocks; with high-voltage symbol, black; yellow

1.1.5 Screwless end stop

1.1.5.1 Mounting accessories



**Item No.: 249-117**  
Screwless end stop; 10 mm wide; for DIN-rail 35 x 15 and 35 x 7.5; gray



**Item No.: 249-116**  
Screwless end stop; 6 mm wide; for DIN-rail 35 x 15 and 35 x 7.5; gray

1.1.6 Strain relief

1.1.6.1 Strain relief plate



**Item No.: 734-326**  
Strain relief plate; for female and male connectors; 35 mm wide; 1 part; gray

1.1.7 Tool

1.1.7.1 Operating tool



**Item No.: 210-719**  
Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft




**Item No.: 210-648**  
Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft; angled; short



**Item No.: 210-647**  
Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft; multicoloured

Installation Notes


Coding



Insert coding pin into the corresponding slot and twist it off.



Coding a female plug: remove coding finger using a suitable tool.



Insert coded female plug into X-COM®S-SYSTEM terminal block assembly.