

Lynx D Series

5.0kWh | High Voltage Battery

GoodWe's Lynx D Series is a high-voltage lithium battery specially designed for residential applications with superior performance. Compatible with GoodWe residential energy storage inverters, Lynx D Series comes with one-stop-shop solutions saving you considerable time and effort. This versatile system serves effectively in scenarios focused on self-consumption and backup power needs. With its sleek and modern design, it seamlessly blends into residential settings. The installation and commissioning have been made quicker and easier than ever with a user-friendly plug and play wiring system. Moreover, Lynx D batteries are engineered to support a mix of old and new battery packs, ensuring adaptable expansion and hassle-free replacement options.



COMING
SOON



Smart Control

- Remote diagnosis and update via inverter
- Auto reboot after undervoltage



Friendly & Thoughtful Design

- Sleek and modern design
- Plug and play wiring



Superb Safety & Reliability

- Reliable LFP technology with high cycle stability
- IP66 protection for outdoor installation safety



Flexible & Adaptable Applications

- Modular design for parallel connection
- Supports mixing new and old battery packs for flexible expansion

Technical Data		LX D5.0-10
Usable Energy (kWh) ¹		5
Cell Type		LFP (LiFePO ₄)
Nominal Voltage (V)		Charge: 435; Discharge: 380
Output Voltage (V)		320 ~ 480
Nominal Power (kW)		3
Peak Power		5kW, 10s
Operating Ambient Temperature Range (°C) ²		Charge: 0 ~ +53; Discharge: -20 ~ +53
Relative Humidity		0 - 95%
Max. Operating Altitude (m)		4000
Communication		CAN
Weight (kg)		52
Dimensions (W x H x D mm)		700 x 380 x 170
Ingress Protection Rating		IP66
Mounting Method		Floor stacked / Wall-mounted
Standard and Certification	Safety	IEC62619, IEC60730, VDE2510-50, CE, CEC
	EMC	CE, RCM
	Transportation	UN38.3

*1: Test conditions, 100% DOD, 0.2C charge & discharge at +25 ±3°C for battery system at beginning life. System Usable Energy may vary with different Inverter.

*2: Load derating may occur due to fluctuations in ambient temperature.

*: Please visit GoodWe website for the latest certificates.

*: All pictures shown are for reference only. Actual appearance may vary.

*: As a part of our policy of continuous improvement, we reserve the right to alter design and specifications without further notice.