

PRODUCT DATASHEET

Type: SET-eFLOOR-LM-S-120-200
Art. Nr.: 46699



9120129934626

Short description

Laminotherm set, PFAS-free, incl. eBASIC controller, 1m², 120W



Product Description

The eFLOOR LM STANDARD floor heating set contains the factory-assembled eFLOOR LM thin-bed heating mat for temperature control of laminate, parquet, and cork floors, as well as for heating well-insulated rooms. The heating mat is laid floating under the floor covering and is suitable for dry indoor areas. The integrated, reinforced aluminum mesh ensures even heat distribution and reliably prevents the formation of hot spots. With a construction height of only 1.3 mm, the mat is particularly suitable for renovations. The magnetic field-free dipole heating conductor minimizes electromagnetic fields, making the eFLOOR LM a low-electrosmog and PFAS-free solution. The heating output is 120 W/m². Nominal temperature: up to 90 °C. Protective measure: FI protective circuit 30 mA. Protection class: IP X7. Construction according to IEC 60335. Connection cable: 4 m, 2×1.0 mm² with protective braiding. Aluminum mesh thickness: 1 mm. CE-compliant and SEMCO-certified. The set also includes the eBASIC switch-in thermostat with a classic rotary knob and integrated Bluetooth function for operation via smartphone or tablet using the eControl app. The device thus offers both analog and smart control options in a timeless design. A sensor protection tube FSH and a 2.5 m long installation hose with a diameter of 12 mm for easy sensor installation are also included in the scope of delivery. Operating voltage: 230 V. A compact, user-friendly solution for electric floor heating systems under sensitive floor coverings.

ETIM 10 Characteristics

| | | | |
|--|-------|----------------------------------|---------------------------|
| Model | Other | Connection voltage | 230 23 Volt 0 |
| With support mat | × | Connected load | 120 12 Watt 0 |
| Fixation thermal conductor | Glued | Power | 120 Watt per square metre |
| Self-adhesive | × | Heating conductor load | 12 Watt per metre |
| Suitable for damp space | ✓ | Resistance | 441 Ohm |
| Suitable as outdoor surface heating | × | Number of cold conductors | 1 |
| Suitable as roof surface heating | × | Length of cold conductors | 4000 Millimetre |
| With controller | ✓ | Surface | 1 Square metre |
| With room temperature controller | ✓ | Length | 2000 Millimetre |
| With floor temperature sensor | ✓ | Width | 500 Millimetre |
| | | Thickness | 1 Millimetre |

Created on: 16/12/2025