


Concord

OPTIX SURFACE 1200x200 2 LINE TW ALU DALI EM

2023765



Features

- OPTIX SURFACE 1200x200 2 LINE TW ALU DALI EM is a high efficacy low glare luminaire for office and education applications. Suitable for surface and suspended mounting. Size: 1129x200x45mm. Aluminised plastic extra low glare optics in 2 lines configuration. White RAL9016 fixture body. DALI DT8 control for colour tuning. 3hr maintained emergency version. Tunable White LED, CRI>80, chromaticity tolerance of 3-step MacAdam ellipse. Luminous flux 3200lm. Power consumption 33W. Luminaire efficacy 97lm/W. Lifespan: 60,000 hours L90B10. UGR<16, Luminance at 65°<200 Cd/m², IK07, IP20. Photobiological safety risk group 0. Electrical protection Class I. Glow wire test 850°C.

Product Overview

Product name	OPTIX SURFACE 1200x200 2 LINE TW ALU DALI EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
Fixture rating	Enclosed
Fixture luminous flux (lm)	3200
Luminaire efficacy (lm/W)	97
Light colour	Tunable White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	85
Total power consumption (W)	33


Concord
by SYLVANIA

Concord

OPTIX SURFACE 1200x200 2 LINE TW ALU DALI EM 2023765

Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768237654
Warranty	5 years

Photometry



Technical drawings

