


**Product data**


|              |                                                                                                                                             |          |                |            |                      |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------|----------|----------------|------------|----------------------|
| Product code | <b>VG03-0054</b>                                                                                                                            | STK-code | <b>1914359</b> | EAN-code   | <b>6430051860331</b> |
| Product name | OJL connector 135 Green                                                                                                                     |          |                | ETIM class | <b>EC000276</b>      |
| Wires        | IN 1x(Al/Cu) 2,5-35 mm <sup>2</sup> / 1x (Al/Cu) 2,5-10 mm <sup>2</sup> OUT: 4x (Cu) 2,5-16mm <sup>2</sup> / 2x (Cu) 2,5-10 mm <sup>2</sup> |          |                |            |                      |

**Technical data**

|                       |                                                                                           |             |                 |
|-----------------------|-------------------------------------------------------------------------------------------|-------------|-----------------|
| Nominal current (IEC) | Cu                                                                                        | <b>135</b>  | A               |
|                       | Al                                                                                        | <b>120</b>  | A               |
| Nominal voltage (IEC) |                                                                                           | <b>1000</b> | V               |
|                       |                                                                                           | -           |                 |
|                       |                                                                                           | -           |                 |
|                       |                                                                                           | -           |                 |
| Number of poles       |                                                                                           | <b>1</b>    | pcs             |
| Max. Cross section    |                                                                                           | <b>35</b>   | mm <sup>2</sup> |
| Tightening torque     |                                                                                           |             |                 |
|                       | 2,5-16 mm <sup>2</sup> (M6)                                                               | <b>3</b>    | Nm              |
|                       | 25-35 mm <sup>2</sup> (M8)                                                                | <b>6</b>    | Nm              |
|                       |                                                                                           | -           |                 |
|                       |                                                                                           | -           |                 |
| Input                 | <b>1x Al/Cu 2,5-35 mm<sup>2</sup>, 1x Al/Cu 2,5-10 mm<sup>2</sup></b>                     |             |                 |
| Output                | <b>4x Cu 2,5-16 mm<sup>2</sup>, 2x Cu 2,5-10 mm<sup>2</sup></b>                           |             |                 |
|                       |                                                                                           | -           |                 |
| Operating temperature |                                                                                           | <b>80</b>   | °C              |
| Weight                |                                                                                           | <b>78</b>   | g               |
| IP-protection         |                                                                                           | <b>IP20</b> |                 |
| Standards             | <b>EN IEC 61238-1:2019; EN 60947-7-1:2009;EN 60947-7-2:2009</b>                           |             |                 |
| Color / Material      | <b>Green Cover PC, Grey Housing RAL 7035 PA66/V0, Connector part tin plated aluminium</b> |             |                 |
| Mounting / Connection | <b>Din rail and 2x screw (M5) mounting</b>                                                |             |                 |


**Description**

The single pole distribution block for branching connection. Distribution block with 2 inputs and it will distribute the current through 6 output cables. Connector is made from tin plated aluminium and housing is PA66 V0.

**Drawing**

**Package**

|             |            |               |            |             |             |
|-------------|------------|---------------|------------|-------------|-------------|
| Package     | <b>Box</b> | Pcs / Package | <b>36</b>  | Weight [kg] | <b>2,90</b> |
| Length [mm] | <b>285</b> | Width [mm]    | <b>180</b> | Height [mm] | <b>115</b>  |

**Ouneva Oy**

Teollisuustie 21  
FI-82730 Tuupovaara  
Finland

[www.ounevagroup.fi](http://www.ounevagroup.fi)
[www.ounevaproducts.fi](http://www.ounevaproducts.fi)