

## Data Sheet | Item Number: 895-1600

Marker card; white

<https://www.wago.com/895-1600>



Color: ■ white

### Marking WINSTA® IDC

Choose proven sustainability for the electrical installation at your construction site: The marking from the WINSTA® IDC product line. An extensive range of accessories complements the WINSTA® product line from WAGO.

Lower costs through fast commissioning and elimination of service expenses – solutions from WINSTA® IDC

WINSTA® is the pluggable connection system that is perfectly tailored to the strict requirements of electrical installation. It offers error-free installation of cables and components, quickly and reliably. Take advantage of the pluggable version of our maintenance-free spring pressure connection technology too! Plan your installation with with protection against mismatching from WAGO.

- products perfectly tailored to your requirements guarantee safe use
- convenient installation and commissioning

### Notes

General safety information

#### **NOTICE: Observe installation and safety instructions!**

- Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden!
- Nicht unter Spannung/Last installieren!
- Nur für bestimmungsgemäßen Gebrauch einsetzen!
- Nationale Vorschriften/Normen/Richtlinien beachten!
- Technische Daten der Produkte beachten!
- Auf die richtige Polbelegung achten!
- Keine beschädigten/verschmutzten Komponenten verwenden!
- Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten!
- Leiter bis zum Anschlag einführen!
- Nur mit Verriegelungsklinke und Zugentlastung verwenden!
- Originalzubehör verwenden!

**To be sold only with installation instructions!**

### Physical data

Width	12 mm / 0.472 inches
Height	1 mm / 0.039 inches
Depth	27 mm / 1.063 inches

### Mechanical data

Suitable	for supply and tap-off modules
----------	--------------------------------

### Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	white
Flammability class per UL94	V0
Fire load	0 MJ
Weight	0.5 g

### Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

### Commercial data

Product Group	20 (Winsta)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	CH
GTIN	4045454192884
Customs tariff number	39199080888

### Product Classification

UNSPSC	39121708
eCl@ss 10.0	27-14-11-37
eCl@ss 9.0	27-14-11-37
ETIM 9.0	EC000761
ETIM 10.0	EC000761
ECCN	NO US CLASSIFICATION

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product  
Compliance 895-1600



CAD/CAE-Data

CAE data

EPLAN Data Portal  
895-1600

