

Product data sheet

Item No. 96.032.4053.0

Male connector with strain relief RST20i3S S1 ZR1 V  
GL

Connector RST20i3, 3 pole, male, screw connection, 250V/20A,  
for cable diameters 6-10 mm, color of coding: light gray, color of  
housing: light gray



Item No.	96.032.4053.0
EAN	4015573769694
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

**General**

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pull relief	Yes
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Light grey
Marking of poles	

**Connection Data**

Connection cross section solid	4 mm <sup>2</sup>
Connection cross section stranded	4 mm <sup>2</sup>
Terminations per pole	1

**Model**

Model	male
Number of poles	3

Connection type	Screw connection
Degree of protection (IP)	IP66/IP68

**Material**

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

**Dimensions**

Length	80.4 mm
Width	34.6 mm
Height	34.6 mm

**Technical drawing**

Schnitt A-A  
section A-A

for cable diameter 6-10mm  
für Kabeldurchmesser 6-10mm

M1:1

Verpackungseinheit: je 100 Stück  
packaging unit: per 100

Teile-Nr./ part-nr.	Farbe:/ color:	Einz.-Tl.-Nr.: *1/ single-part-nr.: *1	Preis/Einzelnr. nach	Maßstab	Werkstoff und Oberfläche material and surface Farbe: siehe Tabelle color: see table	ISO - Zeichnung, keine Anmerkungen 2004	Tag	Werk	1. Rev. / Änderung	Zeichnung Nr.	Bl. /	von /
96.032.4053.1	schwarz, ähnl. RAL 9005/ black, similar to RAL 9005	.....1	/	1:1			27.01.	Kelch	T	96.032.4053.0 01K	a	
96.032.4053.0	lichtgrau, ähnl. RAL 7035/ lightgrey, similar to RAL 7035	.....0	/									

Wieland  
elektrotechnische  
Verbindungen

Type  
RST201.3  
S SI ZBT V

Bezeichnung  
STECKERTEIL MIT ZUGENTLASTUNG  
male connector with cord grip  
screw connection without wire protection/Schraubsteck ohne Drahtschutz