

Optix Surface 1200 Direct Medium Output SylSmart
OPTIX SURFACE 1200x200 2 LINE TW ALU SSC EM
2023767







PRODUCT OVERVIEW

Product name	OPTIX SURFACE 1200x200 2 LINE TW ALU SSC EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
Fixture rating	Enclosed
Warranty	5 years
Fixture luminous flux (lm)	3200
Luminaire efficacy (lm/W)	94
Light colour	Tuneable White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 16
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	85
Total power consumption (W)	34
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768237678

PHOTOMETRY

Optix Surface 1200 Direct Medium Output SylSmart OPTIX SURFACE 1200x200 2 LINE TW ALU SSC EM 2023767



TECHNICAL DRAWINGS

