

Rail & Trunk System - Electronic inserts RTS 1.5M 70W 12C NR DD CB 0042602




PRODUCT OVERVIEW

Product name	RTS 1.5M 70W 12C NR DD CB
Technology	LED
Cap/Base	N/A
Housing	Steel
Warranty	5 years
Fixture luminous flux (lm)	11200
Luminaire efficacy (lm/W)	160
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Photobiological Risk Group	RG1
Total power consumption (W)	70
Electrical protection	Class I
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5410288426020

PHOTOMETRY

Rail & Trunk System - Electronic inserts RTS 1.5M 70W 12C NR DD CB 0042602




0.5	0.95 0.22	E(0°) E(90°) E(180°)	4626 8800 2261
1.0	1.96 0.45	E(0°) E(90°) E(180°)	1209 2416 613
1.5	2.97 0.67	E(0°) E(90°) E(180°)	6471 964 254
2.0	3.96 0.99	E(0°) E(90°) E(180°)	3071 654 163
2.5	4.95 1.34	E(0°) E(90°) E(180°)	1999 354 97
3.0	5.94 1.54	E(0°) E(90°) E(180°)	1358 248 67

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 90°)
— C90 - C270 (Half beam angle: 90°)

TECHNICAL DRAWINGS



L 600 900 1202 1500 2403 3000 3605 4500