



SBSKu-EM-H0



Product description:

SBSKu-EM-H0 is a special plastic push-fit elbow, with one pre-moulded coupling, in grey (RAL 7035), non-flame propagating, zero halogen.

This push-fit elbow is used for FPKu-EM-F-H0 straight length plastic conduits. An advantage is that it does not contain halogens that prevents that dangerous toxic and corrosive gases are generated.



VDE 0605
DIN EN 61386-21
classification: 335212
minimum compressive strength: 750 N/5 cm
100 % zero halogen according to DIN VDE V 0604-2-100



Cat. No.:	Type	Inside Ø mm	Outside Ø mm	Content	PU	Weight PU/kg	Bend radius
232 60 016	16	13,0	16	25	PCS	0,375	55
232 60 020	20	16,8	20	25	PCS	0,675	80
232 60 025	25	21,5	25	25	PCS	1,200	120
232 60 032	32	28,0	32	25	PCS	1,700	155
232 60 040	40	35,5	40	25	PCS	3,225	185
232 60 050	50	45,2	50	10	PCS	2,250	200
232 60 063	63	57,8	63	5	PCS	1,700	220

Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-21:2011 Conduit systems for cable management - Part 21: Particular requirements - Rigid conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

Outside diameter according to DIN EN 60423 / IEC 60423

All dimensions without tolerances are for information only.

FRÄNKISCHE ROHRWERKE Gebr. Kirchner GmbH & Co. KG | Hellinger Str. 1 | 97486 Königsberg/Bayern
Hotline +49 9525 88-8123 | Fax +49 9525 88-2151 | info.elektro@fraenkische.com | www.fraenkische.com

Subject to change without notice.

Page 1 of 2

Last modified: 30.05.17



SBSKu-EM-H0

Material properties		Fields of application	
Zero halogen	DIN VDE V 0604-2-100	• on plaster	• machines
Low smoke	DIN EN 61034-2	under plaster	• hot asphalt
Non-flame propagating	DIN EN 61386-1	• on wood	• under screed
UV-resistant	DIN 53387	underground installation	• prefabricated construction
Highspeed		in concrete	• outdoor

Chemical properties	
Resistant to	liquid ammonia, gaseous ammonia, gaseous dry chlorine, photographic developer, vinegar (wine vinegar), aqueous uric acid, sea water, nitric acid, hydrochloric acid, sulfuric acid
Limitedly resistant to	hydrochloric acid emissions, sulphuric acid emissions, gasoline, beer, diesel fuel, methanol, milk, mineral oil, vegetable and animal oils, detergent
Not resistant to	-

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-21 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

