

**IPSWP02NA****REPEATER, 2 GIGABIT POE-POORTEN, IP67**

PoE repeater 10/100/1000Mbps, standaard IEEE802.3af/at/bt. 1 RJ45 ingang 95W max, twee RJ45 uitgangen 30W elk, bereik tot 100m. Plug-and-play bediening en bedieningsindicator. Bedrijfstemperatuur van -20°C tot 60°C, waterproof IP67, vandalproof IK10.



IPSWP02NA

REPEATER, 2 GIGABIT POE-POORTEN, IP67

BELANGRIJKSTE KENMERKEN

Standard IEEE802.3	IEEE802.3, IEEE802.3ab/at/af/bt, IEEE802.3u, IEEE802.3x
LAN PoE poorten	1 IN (PD 10/100/1000 Mbit/s, 95W, IEEE802.3bt), 2 OUT (2 x PSE 10/100/1000 Mbit/s, 2 x 30W, IEEE802.3at/af)

ALGEMENE GEGEVENS

Hoogte (mm)	44
Breedte (mm)	150
Diepte (mm)	73
Type behuizing	Metalen
Productkleur	Staal
Temperatuurbereik (°C)	-20 ÷ 60
Bedrijfsvochtigheid (RH max) (%)	25 ÷ 90

CONNECTIVITEIT

RJ45-poorten (n°)	3
-------------------	---