




Features

- RTS LED linear luminaire for industrial and commercial applications. 1500 mm length with narrow optics provide homogenous light distribution for aisles and focus areas. Fitted with switching EM driver + 3W convertor + BST NICD 4.8V 3.0Ah (Self-contained Version). Steel housing, White color, 0 ... +40 °C operating temperature range, 4000 K, CRI 80, 3 SDMC. 53 W power consumption, 8000 lm luminous flux, 151 lm/W efficacy, 1500 mm x 70.2 mm x 78.6 mm (L x W x H) dimensions, IP20, IK03, 220-240 V 50/60 Hz, Class I. Lifespan L70:B50 120,000 hours.

Product Overview

Product name	RTS 1.5M 50W 8C NR DD 3W 3H EM
Technology	LED
Cap/Base	N/A
Housing	Steel
Fixture luminous flux (lm)	8000
Luminaire efficacy (lm/W)	151
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG1
Total power consumption (W)	53
Electrical protection	Class I
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5410288426044
Warranty	1 year

Technical drawings



L	600	900	1202	1500	2403	3000	3605	4500
---	-----	-----	------	------	------	------	------	------