




## Features

- Compact, energy efficient and exceptional value LED GU10 lamp Same shape and size as halogen GU10 lamp Compact Cluster SMD technology enabling high efficiency with halogen look Reduced visible heat sink from the front Available in 36 degree beam angle High lumen efficacy 15,000 hours average rated life 3 years warranty

## Product Overview

Product name	RefLED ES50 V6 345LM 865 36 SL
Technology	LED
Watt (Rated) (W)	4.2
Cap/Base	GU10
Fixture rating	Open
E-number FI	4741060
Colour temperature (K)	6500
CRI (Ra)	80
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG1
Wattage (W)	4.2
Product EAN number	5410288291703
Warranty	3 years

## Technical drawings



## Data table

### GENERAL DATA

Product name	RefLED ES50 V6 345LM 865 36 SL
Technology	LED
Watt (Rated) (W)	4.2
Cap/Base	GU10
Fixture rating	Open
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
E-number FI	4741060
Warranty	3 years

### OPTICAL DATA

Colour temperature (K)	6500
CRI (Ra)	80
Colour Consistency (SDCM)	6

## RefLED ES50 V6 345LM 865 36 SL 0029170

Colour Variation Initial (SDCM)	6
Luminous Intensity (cd)	770
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

### ELECTRICAL DATA

Wattage (W)	4.2
Equivalent watt (W)	50
Primary Supply/Product voltage - min (V)	220
Control gear required	No
Inrush Current (A)	3.9
Inrush Duration ( $\mu$ s)	4100
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz

### LIFETIME DATA

Lifespan L70 B50	15000
Average life (Rated) (h)	15000

### PHYSICAL DATA

Nominal Product Diameter (mm)	50
Weight (kg)	0.035

### PACKAGING

Single packaging type	Carton
Product EAN number	5410288291703
Packaging single width (cm)	6.1
Packaging single depth (cm)	5.1
DUN14 (inner)	25410288291707
Units per inner package	6
Packaging inner length / height (cm)	9.2
Packaging inner width (cm)	16.4

RefLED ES50 V6 345LM 865 36 SL  
0029170

Packaging inner depth (cm)	13.1
DUN14 (outer)	15410288291700
Packaging outer length / height (cm)	20.8

## SAFETY DATA

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No
Safety message	Not Suitable for totally enclosed fixtures


# SYLVANIA

RefLED ES50 V6 345LM 865 36 SL  
0029170

## Energy label



0029170




5  
kWh/1000h



2019/2015



0029170



5  
kWh/1000h



2019/2015