

Onefold faceplate, for dual USB C charger, Niko Rocker and Niko Toggle, brass dark bronze patina

211-74103

4 year
warranty

The onefold faceplate clicks onto the dual USB-C charger mechanism.

It consists of an upper frame and lower frame that are mechanically interconnected. The upperframe is made of brass. The lower frame is made of anthracite polycarbonate (PC) + acrylic-styrene-acrylate (ASA). The lead concentration in the brass is higher than 0.1% (w/w). The upper frame is 6 mm thick and the lower frame 2 mm.

Niko recommends a design combination with the finishing set in the following colour: .

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Designed to fit the standard dual USB-C charger base



Technical data

Onefold faceplate, for dual USB C charger, Niko Rocker and Niko Toggle, brass dark bronze patina.

- Number of spaces for mechanisms: 1
- Colour faceplate: brass dark bronze patina
- Colour RAL (approximately): 060 40 10
- Colour NCS (approximately): NCS S 7005-Y50R
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material finishing: The upperframe is made of brass. The lower frame is made of anthracite polycarbonate (PC) + acrylic-styrene-acrylate (ASA). The lead concentration in the brass is higher than 0.1% (w/w).
- Surface treatment: patina and protective varnish
- Surface finishing: matt
- Coating upper frame: the upperframe is enamelled bronze
- Coating lower frame: enamelled dark brown
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Surface-mounting height: max. 8.5 mm

- Fire safety:
 - self-extinguishing: complies with a filament test of 650°C
- Halogen-free: yes
- Minimum ambient temperature: -5 °C
- Maximum ambient temperature: 40 °C
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP21D
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 mm x 83 mm x 8.9 mm
- Dimensions visible (HxWxD): 83 mm x 83 mm