

10422500	DATA SHEET	
Valid from: 19.08.2026	EPIC® H-A 3 MAG	

Description

- Innovative metal housing
- For safe connections in the smallest possible space

General characteristics

Series	H-A 3
Version	Panel-mount base
Locking mechanism	Single lever
Protection rating (DIN EN 60529)	IP 66 (latched) IP 68 - 1 meter / 10 hours (latched)
Temperature range	-40 °C to +125 °C



Materials and surfaces

Housing, base material	Zinc die-casting
Housing, surface	Powder-coating, grey
Lever	PA
Gasket	NBR

Standard

Safety Standard	IEC 61984
-----------------	-----------




Versions

Article number	Article description	PU	Lever position
10422500	EPIC® H-A 3 MAG PANEL MOUNT BASE	10	Front
10422501	EPIC® H-A 3 MAG (1)	1	Front
10422502	EPIC® H-A 3 MAG 180°	10	Back

Creator: THB01/PDP Released: TODV1/PDP	Document: DB10422500EN Version: 03	Page 1 of 2
---	---------------------------------------	-------------

10422500	DATA SHEET	
Valid from: 19.08.2026	EPIC® H-A 3 MAG	

Technical Drawings



Industrial machinery and plant engineering



Mechanical resistance



Robust



Waterproof

Info

Compact, robust metal housings size H-A 3

Application range

Machine and equipment manufacturing
Control engineering
Electronic laboratory

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: THB01/PDP Released: TODV1/PDP	Document: DB10422500EN Version: 03	Page 2 of 2
---	---------------------------------------	-------------