

Product data


Product code	VG03-0036	STK-code	1912394	EAN-code	6410019123944
Product name	OJL-connector 400 C Green			ETIM class	EC000276
Wires	1xAl/Cu 95-240/ 3xCu(6-50 mm ²)/ 4xCu(2,5-35mm ²)				

Technical data

Nominal current (IEC)	Cu	600	A
	Al	380	A
Nominal voltage (IEC)		1000	V
		-	
		-	
		-	
Number of poles		1	pcs
Max. Cross section		240	mm ²
Tightening torque			
	2,5-35 mm ²	6	Nm
	6-50 mm ²	10	Nm
	95-240 mm ²	25	Nm
		-	
Input	1x Al/Cu (95-240 mm²)		
Output	3x Cu (6-50 mm²)/ 4x Cu (2,5-35mm²)		
		-	
Operating temperature		80	°C
Weight		250	g
IP-protection		IP20	
Standards	EN 61238-1:2003; EN 60947-7-1:2009		
Color / Material	Green Cover/PC, Grey Housing RAL 7035 PA66/V0, Connector part tin plated aluminium		
Mounting / Connection	DIN rail and 4x screw (M5) mounting		


Description

Single pole distribution block for branching connections. The OJL distribution block is compact and distributes the current through 7 output cables.

Drawing

Package

Package	Box	Pcs / Package	8	Weight [kg]	2,10
Length [mm]	205	Width [mm]	180	Height [mm]	135

Ouneva Oy

Teollisuustie 21
FI-82730 Tuupovaara
Finland

www.ounevagroup.fi
www.ounevaproducts.fi