

Concord

BEACON XL ACCENT 97CRI 3K MEDIUM BEAM L3 ON-BOARD DIM BLACK 2059570



Features

- Integrated LED spotlight, black RAL 9005, compact and minimalist design, low glare, dark-light detail for increased accentuation and visual comfort, ideal for museum, gallery and high-end retail applications, die-cast aluminium body, passive cooling heatsink, beam angle: 33° medium beam, optics: Aluminium reflector, colour temperature: 3000K warm white, total system power: 33W, total fixture output: 2350lm, luminaire efficacy: 71lm/W, LOR: 100%, colour rendering: Ra 97 typical, R9 value at 90, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 850mA, electronic driver, dimmable via on-board potentiometer, power factor: 0.9 electrical protection: CLASS II, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø113x165x205mm, weight: 1.66kg.

Product Overview


Product name	BEACON XL ACCENT 97CRI 3K MEDIUM BEAM L3 ON-BOARD DIM BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
General application	Museums & Galleries, Retail
ETIM Class	EC001744
Fixture luminous flux (lm)	2350
Luminaire efficacy (lm/W)	71
LOR (%)	100
Correlated colour temperature (k)	3000

Concord

BEACON XL ACCENT 97CRI 3K MEDIUM BEAM L3 ON-BOARD DIM BLACK 2059570

Light colour	Warm White
CRI (Ra)	97
Colour Consistency (SDCM)	3
Beam Angle (°)	33
Photobiological Risk Group	RG1
Total power consumption (W)	33
Electrical protection	Class II
Control gear type	Electronic ballast
Minimum dimming level (%)	1
Housing colour	Black
IP rating	IP20
IK rating	IK02
Product EAN number	5025768595709
Warranty	5 years
Dimming method	1-10V (Analogue)
Useful luminous flux (#use)	2350

Photometry



Technical drawings

