

## PRODUCT DATASHEET

### DULUX T/E HF & AC Mains 10 W/4000 K

OSRAM DULUX T/E LED HF & AC MAINS | LED replacement for CFLni with 4-pin GX24q base for ECG



#### Areas of application

- Supermarkets and department stores
- Walkways and corridors
- Hotels, restaurants
- Outdoor applications only in suitable luminaires

#### Product benefits

- Quick, simple and safe replacement
- Low energy consumption
- Operation directly on 230 V AC mains possible

#### Product features

- LED replacement for conventional compact fluorescent lamps for use in ECG luminaires or on AC mains
- Single-ended four-pin plug-in GX24q base
- Rotatable base around its longitudinal axis ( $\pm 90^\circ$ )
- Type of protection: IP20
- Lifetime: up to 30,000 h
- Mercury-free lamps




## TECHNICAL DATA

## Electrical data

|                                          |               |
|------------------------------------------|---------------|
| Nominal wattage                          | 10 W          |
| Construction wattage                     | 10.00 W       |
| Nominal voltage                          | 220...240 V   |
| Operating mode                           | ECG, AC Mains |
| Claimed equiv. conventional lamp power   | 26 W          |
| Nominal current                          | 44 mA         |
| Type of current                          | AC            |
| Inrush current                           | 20 A          |
| Operating frequency                      | 50/60 Hz      |
| Mains frequency                          | 50/60 Hz      |
| Max. lamp no. on circuit break. 10 A (B) | 205           |
| Max. lamp no. on circuit break. 16 A (B) | 325           |
| Total harmonic distortion                | ≤ 30 %        |
| Power factor $\lambda$                   | > 0.90        |

## Photometrical data

|                                         |            |
|-----------------------------------------|------------|
| Luminous flux                           | 1100 lm    |
| Nominal useful luminous flux 90°        | 1100 lm    |
| Luminous efficacy                       | 110 lm/W   |
| Lumen main.fact.at end of nom.life time | 0.70       |
| Light color (designation)               | Cool White |
| Color temperature                       | 4000 K     |
| Color rendering index Ra                | 80         |
| Light color                             | 840        |
| Standard deviation of color matching    | ≤6 sdcn    |
| Flickering metric (Pst LM)              | 1.0        |
| Stroboscope effect metric (SVM)         | 0.4        |




EPREL data spectral diagram PROF  
LEDr 4000K

Light technical data

|                     |          |
|---------------------|----------|
| Beam angle          | 130 °    |
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

Dimensions & Weight



|                  |           |
|------------------|-----------|
| Overall length   | 140.00 mm |
| Diameter         | 45.00 mm  |
| Maximum diameter | 45 mm     |
| Product weight   | 122.00 g  |

Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+50 °C |
| Maximum temperature at tc test point | 80 °C        |

Lifespan

|                                              |         |
|----------------------------------------------|---------|
| Lifespan L70/B50 at 25 °C                    | 30000 h |
| Number of switching cycles                   | 200000  |
| Lumen maintenance at end of service lifetime | 0.70    |
| Rated lamp survival factor at 6,000 h        | ≥ 0.90  |

Additional product data

|                             |         |
|-----------------------------|---------|
| Base (standard designation) | GX24q-3 |
| Mercury content             | 0.0 mg  |
| Design / version            | Frosted |

### Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

### Certificates & Standards

|                                              |                 |
|----------------------------------------------|-----------------|
| Energy efficiency class                      | E <sup>1)</sup> |
| Energy consumption                           | 10.00 kWh/1000h |
| Type of protection                           | IP20            |
| Standards                                    | CE / EAC        |
| Photobiological safety group acc. to EN62778 | RG0             |

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

### Country-specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | DULUXTE26LED 10 |
|-----------------|-----------------|

### Energy labelling regulation data acc EU 2019/2015

|                                                     |              |
|-----------------------------------------------------|--------------|
| Lighting technology used                            | LED          |
| Non-directional or directional                      | NDLS         |
| Mains or non-mains                                  | MLS          |
| Light source cap-type (or other electric interface) | GX24q-3      |
| Connected light source (CLS)                        | No           |
| Color-tuneable light source                         | No           |
| Envelope                                            | No           |
| High luminance light source                         | No           |
| Anti-glare shield                                   | No           |
| Correlated colour temperature type                  | SINGLE_VALUE |
| Standby power                                       | 0 W          |
| Claim of equivalent power                           | No           |
| Length                                              | 140.00 mm    |
| Height                                              | 45.00 mm     |
| Width                                               | 45.00 mm     |
| Chromaticity coordinate x                           | 0.381        |
| Chromaticity coordinate y                           | 0.379        |
| R9 Colour rendering index                           | 0.00         |

|                                                      |            |
|------------------------------------------------------|------------|
| Beam angle correspondence                            | SPHERE_360 |
| Survival factor                                      | 0.90       |
| Displacement factor                                  | 0.90       |
| LED light source replaces a fluorescent light source | No         |
| EPREL ID                                             | 604673     |
| Model number                                         | AC35207    |

### Safety advice

- Always check the latest update of the compatibility list available on [www.ledvance.com/ecg-compatibility](http://www.ledvance.com/ecg-compatibility).
- Not suitable for operation with conventional control gear

### DOWNLOAD DATA

| Documents and certificates                                                         |                                 | Document name       |
|------------------------------------------------------------------------------------|---------------------------------|---------------------|
|    | User instruction                | OSRAM DULUX T/E LED |
|  | Declarations Of Conformity CE   | DULUX lamp          |
|  | Declarations Of Conformity UKCA | DULUX LED           |

| Photometric and lighting design files                                              |                             | Document name                               |
|------------------------------------------------------------------------------------|-----------------------------|---------------------------------------------|
|  | IES file (IES)              | DULUXTE26LED 10W840230VHFGX24Q-3            |
|  | LDT file (Eulumdat)         | DULUXTE26LED 10W840230VHFGX24Q-3            |
|  | LDC typ polar               | DULUXTE26LED 10W840230VHFGX24Q-3            |
|  | Spectral power distribution | EPREL data spectral diagram PROF LEDr 4000K |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075559417 | Folding box<br>1             | 48 mm x 48 mm x 146 mm               | 134.00 g     | 0.34 dm <sup>3</sup> |
| 4058075559424 | Shipping box<br>10           | 246 mm x 102 mm x 157 mm             | 1461.00 g    | 3.94 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.