


BEACON XL ACCENT 97CRI 3K MEDIUM BEAM L3 ON-BOARD DIM WHITE

Item No: 2059571


Concord



Integrated LED spotlight, white RAL 9016, compact and minimalist design, low glare, dark-light detail for increased accentuation and visual comfort, ideal for museum, gallery and high-end retail applications, die-cast aluminium body, passive cooling heatsink, beam angle: 33° medium beam, optics: Aluminium reflector, colour temperature: 3000K warm white, total system power: 33W, total fixture output: 2350lm, luminaire efficacy: 71lm/W, LOR: 100%, colour rendering: Ra 97 typical, R9 value at 90, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 850mA, electronic driver, dimmable via on-board potentiometer, power factor: 0.9 electrical protection: CLASS II, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø113x165x205mm, weight: 1.66kg.

Technical Assets


Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	E ₀ ⁽¹⁾ E _(C0) 16.6°	2309 12170
0.5	0.30	E ₀ ⁽¹⁾ E _(C0) 16.6°	5782 2843
1.0	0.60	E ₀ ⁽¹⁾ E _(C0) 16.6°	289 1130
1.5	0.89	E ₀ ⁽¹⁾ E _(C0) 16.6°	1438 696
2.0	1.19	E ₀ ⁽¹⁾ E _(C0) 16.6°	900 407
2.5	1.49	E ₀ ⁽¹⁾ E _(C0) 16.6°	639 283
3.0	1.79	E ₀ ⁽¹⁾ E _(C0) 16.6°	500 225

Distance [m] Cone diameter [m] Illuminance [lx]
 C0 - C180 (Half beam angle: 33.2°)



BEACON XL ACCENT 97CRI 3K MEDIUM BEAM L3 ON-BOARD DIM WHITE

Item No: 2059571

Concord

General data

Product name	BEACON XL ACCENT 97CRI 3K MEDIUM BEAM L3 ON-BOARD DIM WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
General application	Museums & Galleries, Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Warranty	5 years

Optical data

Useful luminous flux (Φuse)	2350
Fixture luminous flux (lm)	2350
Luminaire efficacy (lm/W)	71
LOR (%)	100
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	97
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	33
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	33
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
Electrical protection	Class II
Control gear type	Electronic ballast
Dimmable	Yes
Dimming method	1-10V (Analogue)
Minimum dimming level (%)	1
Drive current (mA)	850
Inrush Current (A)	20
Inrush Duration (µs)	50
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	85

Lifetime data

Lifespan L70 B50	72000
Lifespan L70 B10	72000
Lifespan L80 B20	72000
Lifespan L80 B10	72000
Lifespan L90 B50	43000
Lifespan L90 B20	36000
Lifespan L90 B10	32000

Physical data

Housing colour	White
IP rating	IP20
IK rating	IK02
Reflector finish	Not Applicable
Nominal Product Width (mm)	165
Nominal Product Height (mm)	205
Nominal Product Diameter (mm)	113
Weight (kg)	3.008

BEACON XL ACCENT 97CRI 3K MEDIUM BEAM L3 ON-BOARD DIM WHITE

Item No: 2059571

Concord

Packaging

Product EAN number	5025768595716
Packaging single length / height (cm)	25.0
Packaging single width (cm)	19.5
Packaging single depth (cm)	20.0
DUN14 (inner)	05025768595716
Units per outer package	1
Packaging outer length / height (cm)	25.0
Packaging outer width (cm)	19.5
Packaging outer depth (cm)	20.0

Safety data

Glow Wire Test (°C)	650
---------------------	-----