

# Specifications

Photo is representative

## Eaton 236279

Eaton Moeller series xPole - PKN6/M RCBO - residual-current circuit breaker with overcurrent protection. RCD/MCB, 25A, 30mA, C-LS-Char, 1N pole, FI-Char: A

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller series xPole - PKN6/M RCBO - residual-current circuit breaker with overcurrent protection
<b>CATALOG NUMBER</b>	236279
<b>MODEL CODE</b>	PKNM-25/1N/C/003-A-MW
<b>EAN</b>	4015082362799
<b>PRODUCT LENGTH/DEPTH</b>	80 mm
<b>PRODUCT HEIGHT</b>	75 mm
<b>PRODUCT WIDTH</b>	35 mm
<b>PRODUCT WEIGHT</b>	0.204 kg
<b>COMPLIANCES</b>	RoHS conform
<b>CERTIFICATIONS</b>	CE
<b>GLOBAL CATALOG</b>	236279
<b>PRODUCT TYPE</b>	RCBO - Residual-current circuit breaker with overcurrent protection



Powering Business Worldwide

## Product specifications

<b>AMPERAGE RATING</b>	25 A
<b>VOLTAGE RATING</b>	230 V
<b>SURGE CURRENT CAPACITY</b>	0.25 kA
<b>VOLTAGE TYPE</b>	AC
<b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>	2
<b>FEATURES</b>	Concurrently switching N-neutral
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL</b>	Does not apply, since the

## Resources

CATALOGS	<a href="#">eaton-xpole-pknm-110va-rcbo-catalog-ca019042en-en-us.pdf</a>
CHARACTERISTIC CURVE	<a href="#">eaton-xpole-pkn6-m-characteristic-curve-005.jpg</a>
DECLARATIONS OF CONFORMITY	<a href="#">eaton-rcbo-residual-current-circuit-breaker-with-overcurrent-protection-declaration-of-conformity-eu250083en.pdf</a>
DRAWINGS	<a href="#">eaton-xpole-pkn6-m-dimensions.jpg</a> <a href="#">eaton-xpole-pkn6-m-3d-drawing.jpg</a>
ECAD MODEL	<a href="#">ETN.PKNM-25_1N_C_003-A-MW</a>
INSTALLATION INSTRUCTIONS	<a href="#">eaton-rccb-rcbo-g9-il019140zu.pdf</a>
MCAD MODEL	<a href="#">eaton-rcd-with-overcurrent-protection-3d-models-fk9051.stp</a> <a href="#">eaton-rcbo-mcad-drawings-fk9051.dwg</a>
PEP ECO-PASSPORT	<a href="#">eaton-rcd-with-overcurrent-protection-pep-eato-00114-v0101-en.pdf</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - 236279</a>
WIRING DIAGRAMS	<a href="#">FL7</a>

<b>IMPACT</b>	entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>OPERATING AMBIENT TEMPERATURE - MAX</b>	40 °C
<b>OPERATING AMBIENT TEMPERATURE - MIN</b>	-25 °C
<b>PRODUCT RANGE</b>	PKNM
<b>RATED CURRENT</b>	25 A
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	25 A
<b>RATED SWITCHING CAPACITY (IEC/EN 61009)</b>	10 kA
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT</b>	0 W
<b>TRIPPING CHARACTERISTIC</b>	C
<b>BUILT-IN DEPTH</b>	70 mm
<b>CURRENT LIMITING CLASS</b>	3
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60947-2)</b>	0 kA
<b>AMBIENT OPERATING</b>	40 °C

<b>TEMPERATURE - MAX</b>	
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>FAULT CURRENT RATING</b>	0.03 A
<b>HEAT DISSIPATION CAPACITY</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT</b>	0 W
<b>NUMBER OF POLES (PROTECTED)</b>	1
<b>NUMBER OF POLES (TOTAL)</b>	2
<b>RATED OPERATIONAL VOLTAGE (UE) - MAX</b>	230 V
<b>RATED SWITCHING CAPACITY</b>	10 kA
<b>BASIC FUNCTION</b>	Combined RCD/MCB devices
<b>MOUNTING METHOD</b>	DIN rail
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>	4.8 W
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	4 kV
<b>DEGREE OF PROTECTION</b>	IP20
<b>TRIPPING</b>	Non-delayed
<b>OVERVOLTAGE CATEGORY</b>	III
<b>POLLUTION DEGREE</b>	2
<b>IMPULSE WITHSTAND CURRENT</b>	Partly surge-proof, 250 A
<b>LEAKAGE CURRENT TYPE</b>	A
<b>RELEASE CHARACTERISTIC</b>	C
<b>SENSITIVITY TYPE</b>	Type A, pulse-current sensitive
<b>FREQUENCY RATING</b>	50 Hz
<b>RATED INSULATION VOLTAGE (UI)</b>	440 V
<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN</b>	1 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX</b>	25 mm <sup>2</sup>

<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN</b>	1 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX</b>	25 mm <sup>2</sup>
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 61009)</b>	10 kA
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 61009-1)</b>	10 kA
<b>NUMBER OF POLES</b>	Single-pole + N
<b>DISCONNECTION CHARACTERISTIC</b>	Undelayed
<b>TYPE</b>	RCBO
<b>APPLICATION</b>	Switchgear for residential and commercial applications

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc** Eaton House  
 30 Pembroke Road  
 Dublin 4, Ireland  
 Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

