

Features

• OPTIX LINEAR RECESSED 1200 4000K ALU SSC EM is a high efficacy low glare linear luminaire for office and education applications. Suitable for continuous light line installations with accessories separately available. Ceiling recessed 1169x95x90 mm. Aluminised plastic extra low glare optics in a single line configuration. White RAL9016 fixture body. SylSmart Stand-alone Office capable. 3hr maintained emergency version. 4000K Neutral White LED, CRI>80, chromaticity tolerance of 3-step MacAdam ellipse. Luminous flux 3400lm. Power consumption 29W. Luminaire efficacy 117lm/W. Lifespan: 48,500 hours L90B10. UGR<19, Luminance at 65°<200 Cd/m2, IK07, IP20. Ultra Low Flicker: <5% Photobiological safety risk group 1. Electrical protection Class I. Glow wire test 850°C. Suitable for use with Linect quick connection systems.


Product Overview

Product name	OPTIX LINEAR RECESSED 1200 4000K ALU SSC EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Fixture luminous flux (lm)	3400
Luminaire efficacy (lm/W)	117
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3


OPTIX LINEAR RECESSED 1200 4000K ALU SSC EM
2023790

Glare control	< 19
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	80
Total power consumption (W)	29
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768237906
Warranty	5 years


Photometry



OPTIX LINEAR RECESSED 1200 4000K ALU SSC EM 2023790



Technical drawings



Data table

GENERAL DATA

Product name	OPTIX LINEAR RECESSED 1200 4000K ALU SSC EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Operating temperature range (°C)	10°C...+25°C
Performance ambient temperature Tq (°C)	25

OPTIX LINEAR RECESSED 1200 4000K ALU SSC EM 2023790

Warranty	5 years
----------	---------

OPTICAL DATA

Fixture luminous flux (lm)	3400
Luminaire efficacy (lm/W)	117
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	80
Emergency duration (h)	3

ELECTRICAL DATA

Total power consumption (W)	29
Primary Supply/Product voltage - min (V)	198.0
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	500
Inrush Current (A)	20
Inrush Duration (µs)	25
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	57
Max. products per 20A B Breaker	68
Connectable conductor cross section - Min (mm²)	2.5

OPTIX LINEAR RECESSED 1200 4000K ALU SSC EM 2023790

Connectable conductor cross section - Max (mm²)	2.5
--	-----

LIFETIME DATA

Lifespan L70 B50	120000
Lifespan L80 B20	107500
Lifespan L90 B10	48500

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1169
Nominal Product Width (mm)	95
Weight (kg)	3.15

PACKAGING

Single packaging type	Carton
Product EAN number	5025768237906
Packaging single width (cm)	10.0
Packaging single depth (cm)	11.0
DUN14 (outer)	05025768237906
Packaging outer length / height (cm)	119.0

SAFETY DATA

Optimal operating condition (°C)	10-25
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No