

Concord

MC2 D/I 2.4M 4K DALI BLK PRIS 2071554



Features

- MC2 D/I 2.4M 4K DALI BLK PRIS LED luminaire, black RAL9005 finishing, direct/indirect distribution (65/35), various accessories available, compact and minimalist design based on the Golden Mean, ideal for offices, meeting rooms, corridors, education facilities, museums and libraries, extruded aluminium body, diffuser: micro prismatic, colour temperature: 4000K neutral white, total system power: 58W, total fixture output: 7700lm, luminaire efficacy: 133m/W, LOR: 100%, colour rendering: Ra >80, LED Chromacity: 3 step MacAdam ellipse, lifespan: 66,000 hours L90B10, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: (Direct) 800mA + (Indirect) 350mA, electronic driver, DALI dimmable, direct/indirect independently addressable, electrical protection: CLASS I, IP20, suitable for internal environment only.

Product Overview


Product name	MC2 D/I 2.4M 4K DALI BLK PRIS
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
General application	Education, Hospitality, Office, Retail
ETIM Class	EC001743
E-number FI	4170319
Fixture luminous flux (lm)	7700
Luminaire efficacy (lm/W)	133
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3

Concord

MC2 D/I 2.4M 4K DALI BLK PRIS 2071554

Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	58
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	1
Housing colour	Black
IP rating	IP20
IK rating	IK03
Product EAN number	5025768715541
Warranty	5 years
Useful luminous flux (#use)	7700
Dimming method	DALI

Photometry



Technical drawings

