

Threefold faceplate, horizontal 71 mm centre distance, for a single and a double switch function and one 45x45 function, Niko Rocker alu ganache brushed

222-56723

4 year
warranty

The Niko Rocker threefold horizontally oriented faceplate clicks onto a single and a double switch function and one 45x45 function that have been horizontally installed next to each other with a centre distance of 71 mm. The faceplate combines with any available Niko Rocker for single and double switch functions and Niko 45 x 45 mm finishing set. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upperframe is made of aluminium. The lower frame is made of anthracite polycarbonate (PC) + acrylic-styrene-acrylate (ASA). The upper frame is 6 mm thick and the lower frame 2 mm.



Niko recommends a design combination with a finishing set in the following colour: alu ganache for Niko Rocker and Niko Toggle finishing sets and dark brown coated for other finishing sets.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)
- Designed to fit any available 45 x 45 mm function

Technical data

Threefold faceplate, horizontal 71 mm centre distance, for a single and a double switch function and one 45x45 function, Niko Rocker alu ganache brushed.

- Number of spaces for mechanisms: 3
- Colour faceplate: alu ganache brushed
- Colour RAL (approximately): 050 30 10
- Colour NCS (approximately): NCS S 8005-Y50R
- Recommended colour central plate: alu ganache for Niko Rocker and Niko Toggle finishing sets and dark brown coated for other finishing sets
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material finishing: The upperframe is made of aluminium. The lower frame is made of anthracite polycarbonate (PC) + acrylic-styrene-acrylate (ASA).

- Surface treatment: anodised and brushed. The anodisation process may result in slight colour differences
- Surface finishing: matt
- Coating upper frame: enamelled ganache
- Coating lower frame: enamelled dark brown
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Surface-mounting height: max. 8.5 mm
- Fire safety:
 - self-extinguishing: complies with a filament test of 650°C
- Centre-to-centre distance: 71 mm
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP20D
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 mm x 225 mm x 13 mm
- Dimensions visible (HxWxD): 83 mm x 225 mm