

ToLEDo Superia T5 ECG

TOLEDO SUPERIA T5 HO 5FT 5150LM 830

0029516



Product features

- 60,000 hours average rated lifetime (L70 F50). Last 3 times longer than 80W 1449mm fluorescent tri-phosphor T5 lamp. High switching cycles - 200,000X. High lumen efficacy -139lm/W. Omni-directional light distribution and wide beam angle. Minimum and maximum operating temperature: -20°C to 50°C. Glass construction and polycarbonate end-caps. Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast. Works only with compatible electronic ballasts. Ideal for factories, parking lots, supermarkets, department stores, schools and offices.



PRODUCT OVERVIEW

Product name	TOLEDO SUPERIA T5 HO 5FT 5150LM 830
Technology	LED
Watt (Rated) (W)	37
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4740613
E-number SE	8293586
Warranty	5 years
Useful luminous flux (Fuse)	5150
Luminous flux (lm)	5150
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Beam Angle (°)	220
Power consumption (W)	37
Wattage (W)	37
Dimmable	No
Average life (Nominal) (h)	60000
Product EAN number	5410288295169