



Features

- L-shape connection unit for opal diffuser version of Otao Linear range, RAL9011 (black) finishing, direct distribution, only 3000K/4000K LED light sources included, feed by next straight luminaire, shipped with 2x fast connectors and additional replacement electrical connectors, 50mm wide extruded aluminium profile, nominal size: 170x170x50x73mm.

Product Overview

Product name	OTAO LINEAR CORN-L OPAL 830/840 BK
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting, Ceiling surface mounting, Suspended, Wall surface mounted
General application	Office, Education
ETIM Class	EC002556
E-number FI	4170663
Fixture luminous flux (lm)	600
Luminaire efficacy (lm/W)	122
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	110
Glare control	< 28

OTAO LINEAR CORN-L OPAL 830/840 BK 0040809

Photobiological Risk Group	RG0
Total power consumption (W)	4.9
Electrical protection	Class III
Dimmable	No
Housing colour	RAL9011
IP rating	IP20
IK rating	IK03
Product EAN number	5410288408095
Warranty	5 years
Dimming method	N/A

Technical drawings

