



Features

- X-shape connection unit for opal diffuser version of Otao Linear range, RAL9011 (black) finishing, direct distribution, only 3000K/4000K LED light sources included, feed by next straight luminaire, shipped with 4x fast connectors and additional replacement electrical connectors, 50mm wide extruded aluminium profile, nominal size: 290x290x50x73mm.

Product Overview

Product name	OTAO LINEAR CORN-X OPAL 830/840 BK
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting, Ceiling surface mounting, Wall surface mounted, Suspended
General application	Office, Education
ETIM Class	EC002556
E-number FI	4170665
Fixture luminous flux (lm)	1250
Luminaire efficacy (lm/W)	128
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	110
Glare control	< 28

OTAO LINEAR CORN-X OPAL 830/840 BK 0040811

Photobiological Risk Group	RG0
Total power consumption (W)	9.8
Electrical protection	Class III
Dimmable	No
Housing colour	RAL9011
IP rating	IP20
IK rating	IK03
Product EAN number	5410288408118
Warranty	5 years
Dimming method	N/A

Technical drawings

