



Features

- 50,000 hours average rated life (L70 F50)
- Last 2.5 times longer than 1500mm 58W fluorescent T8 Tri-phosphor lamp
- High switching cycles – 200,000X
- High lumen efficacy - 150lm/W
- Omni-directional light distribution and wide beam angle
- Minimum and maximum operating temperature: -20°C to 55°C
- Glass construction and polycarbonate end-caps
- Not suitable for direct mains (AC 220-240V) or CCG/magnetic ballast
- Works only with compatible electronic ballast
- Ideal for factories, parking lots, supermarkets, department stores, schools and offices.

Product Overview

Product name	TOLEDO SUPERIA T8 ECG 5FT 3100LM 865
Technology	LED
Watt (Rated) (W)	20.6
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4740677
Luminous flux (lm)	3100
Correlated colour temperature (k)	6500
CRI (Ra)	80
Beam Angle (°)	220
Wattage (W)	20.6
Power consumption (W)	20.6
Average life (Nominal) (h)	50000
Product EAN number	5410288270890
Warranty	5 years
Useful luminous flux (#use)	3100

Data table

TOLEDO SUPERIA T8 ECG 5FT 3100LM 865 0027089

GENERAL DATA

Product name	TOLEDO SUPERIA T8 ECG 5FT 3100LM 865
Technology	LED
Watt (Rated) (W)	20.6
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740677
Warranty	5 years

OPTICAL DATA

Useful luminous flux (#use)	3100
Luminous flux (lm)	3100
Luminous flux (Rated) (lm)	3100
Correlated colour temperature (k)	6500
CRI (Ra)	80
Beam Angle (°)	220
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Power consumption (W)	20.6
Wattage (W)	20.6
Starting time (max) (s)	0.5
Primary Supply/Product voltage - min (V)	45
Lamp power factor	0.88
Control gear required	No
kWh per 1000 hours burning time	23

LIFETIME DATA

TOLEDO SUPERIA T8 ECG 5FT 3100LM 865 0027089

Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

PHYSICAL DATA

Nominal Product Diameter (mm)	1500
Weight (kg)	0.305

PACKAGING

Product EAN number	5410288270890
Packaging single width (cm)	2.9
Packaging single depth (cm)	2.9
DUN14 (inner)	15410288270897
Packaging outer length / height (cm)	157.5

SAFETY DATA

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No
Safety message	Suitable for totally enclosed fixture