

OPTIX LINEAR RECESSED 1200 TW ALU SSC 2023795



Features

• OPTIX LINEAR RECESSED 1200 TW ALU SSC is a high efficacy low glare linear luminaire for office and education applications. Suitable for continuous light line installations with accessories separately available. Ceiling recessed 1146x95x90 mm. Aluminised plastic extra low glare optics in a single line configuration. White RAL9016 fixture body. SylSmart Standalone colour control and dimming. Tunable white colour 3000-6000K, CRI>80, chromaticity tolerance of 3-step MacAdam ellipse. Luminous flux 2200lm. Power consumption 22W. Luminaire efficacy 100lm/W. Lifespan: 48,500 hours L90B10. UGR<19, Luminance at 65°<200 Cd/m2, IK07, IP20. Ultra Low Flicker: <5% Photobiological safety risk group 1. Electrical protection Class I. Glow wire test 850°C. Suitable for use with Linect quick connection sytems.


Product Overview

Product name	OPTIX LINEAR RECESSED 1200 TW ALU SSC
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Fixture luminous flux (lm)	2200
Luminaire efficacy (lm/W)	105
Light colour	Tuneable White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG1
Total power consumption (W)	22
Electrical protection	Class I


OPTIX LINEAR RECESSED 1200 TW ALU SSC
2023795

Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768237951
Warranty	5 years

Photometry



Technical drawings



Data table

GENERAL DATA

OPTIX LINEAR RECESSED 1200 TW ALU SSC 2023795

Product name	OPTIX LINEAR RECESSED 1200 TW ALU SSC
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Operating temperature range (°C)	10°C...+25°C
Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	2200
Luminaire efficacy (lm/W)	105
Correlated colour temperature range (K)	3000 - 6000
Light colour	Tuneable White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	22
Primary Supply/Product voltage - min (V)	198.0
Lamp power factor	0.97
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	400
Inrush Current (A)	29
Inrush Duration (µs)	180
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	D

OPTIX LINEAR RECESSED 1200 TW ALU SSC 2023795

Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 20A B Breaker	27
Connectable conductor cross section - Min (mm ²)	2.5
Connectable conductor cross section - Max (mm ²)	2.5

LIFETIME DATA

Lifespan L70 B50	120000
Lifespan L80 B20	107500
Lifespan L90 B10	48500

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1146
Nominal Product Width (mm)	95
Weight (kg)	3.15

PACKAGING

Single packaging type	Carton
Product EAN number	5025768237951
Packaging single width (cm)	10.0
Packaging single depth (cm)	11.0
DUN14 (outer)	05025768237951
Packaging outer length / height (cm)	119.0

SAFETY DATA

Concord

OPTIX LINEAR RECESSED 1200 TW ALU SSC 2023795

Optimal operating condition (°C)	10-25
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No