



Color: ■ black

Power supply is performed via 10 inline splicing connectors with levers 221-2411.

Application example: blind drives control

Includes: one cable clamp and two mounting screws

Electrical data

Ratings per IEC/EN

Nominal voltage (III/3) 400 V

Rated impulse withstand voltage (III / 3) 6 kV

Rated current 16 A

Ratings per IEC/EN 2

Rated voltage (III / 3) 250 V

Rated impulse withstand voltage (III/3) 4 kV

Connection data

Connection 1

Connection type Input

Connection 2

Connection type Output
Connector MIDI socket, 4-pole (770-204)

Physical data

Width

190 mm / 7.48 inches

Height

30 mm / 1.181 inches

Depth

145 mm / 5.709 inches

Mechanical data

Internal wiring

1.5 mm²

Use

Supply cable entry

Coding

A

Mounting type

Wall, screw mount
Installation on mounting plate

Material data

Note (material data)	Information on material specifications can be found here
Color	black
Contact Plating	Tin
Fire load	17.938 MJ
Weight	323.8 g

Environmental requirements

Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C
--	---

Commercial data

PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4066966816273
Customs tariff number	85366990990

Product Classification

UNSPSC	39121406
ETIM 9.0	EC002567
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

[Compliance Search](#)Environmental Product
Compliance
899-631/460-000

1 Compatible Products

1.1 System counterpart

1.1.1 Cable assembly

[Item No.: 771-9994/206-101](#)pre-assembled connecting cable; Eca;
Plug/open-ended; 4-pole; Cod. A; H05VV-
F 4G 1.5 mm²; 1 m; 1,50 mm²; black[Item No.: 771-9994/006-101](#)pre-assembled interconnecting cable;
Eca; Socket/plug; 4-pole; Cod. A; H05VV-
F 4G 1.5 mm²; 1 m; 1,50 mm²; black

1.1.2 Male connector/plug



[Item No.: 770-214](#)

Plug; 4-pole; Cod. A; 4,00 mm²; black



[Item No.: 770-114](#)

Plug; with strain relief housing; 4-pole;
Cod. A; 4,00 mm²; black

1.2 Optional Accessories

1.2.1 Installation

1.2.1.1 Mounting accessories



[Item No.: 899-680](#)

Mounting plate; for distribution boxes; gray