



Features

- 60,000 hours average rated lifetime (L70 F50). Last 3 times longer than 54W 1149mm fluorescent tri-phosphor T5 lamp. High switching cycles – 200,000X. High lumen efficacy -152lm/W. Omni-directional light distribution and wide beam angle. Minimum and maximum operating temperature: -20°C to 50°C. Glass construction and polycarbonate end-caps. Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast. Works only with compatible electronic ballasts. Ideal for factories, parking lots, supermarkets, department stores, schools and offices.

Product Overview

Product name	TOLEDO SUPERIA T5 HO 4FT 4100LM 840
Technology	LED
Watt (Rated) (W)	27
General application	Office, Hospitality, Retail, Logistics & Industry, Education, Residential & Consumer, Museums & Galleries
ETIM Class	EC001959
E-number FI	4740605
E-number SE	8293578
Luminous flux (lm)	4100
Correlated colour temperature (k)	4000
CRI (Ra)	80
Beam Angle (°)	220
Wattage (W)	27
Power consumption (W)	27
Average life (Nominal) (h)	60000
Product EAN number	5410288295084
Warranty	5 years
Useful luminous flux (#use)	4100

SYLVANIA

TOLEDO SUPERIA T5 HO 4FT 4100LM 840
0029508



Light your world