



Features

- 60,000 hours average rated lifetime (L70 F50). Last 3 times longer than 49W 1449mm fluorescent tri-phosphor T5 lamp. High switching cycles – 200,000X. High lumen efficacy -156lm/W. Omni-directional light distribution and wide beam angle. Minimum and maximum operating temperature: -20°C to 50°C. Glass construction and polycarbonate end-caps. Not suitable for direct mains (AC 220-240V) or magnetic/CCG ballast. Works only with compatible electronic ballasts. Ideal for factories, parking lots, supermarkets, department stores, schools and offices.

Product Overview

Product name	TOLEDO SUPERIA T5 HO 5FT 4050LM 830
Technology	LED
Watt (Rated) (W)	26
General application	Office, Hospitality, Retail, Logistics & Industry, Education, Residential & Consumer, Museums & Galleries
ETIM Class	EC001959
E-number FI	4740610
E-number SE	8293583
Luminous flux (lm)	4050
Correlated colour temperature (k)	3000
CRI (Ra)	80
Beam Angle (°)	220
Wattage (W)	26
Power consumption (W)	26
Average life (Nominal) (h)	60000
Product EAN number	5410288295138
Warranty	5 years
Useful luminous flux (#use)	4050

SYLVANIA

TOLEDO SUPERIA T5 HO 5FT 4050LM 830
0029513



Light your world